

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Mass Air Flow Sensor	P0100	range check low range check high	value	see table KFMLDMN (4...152,8 kg/h) see table KFMLDMX (141...885 kg/h)	battery voltage time after start Errorflag throttle position sensor	> 11 V > 0,3 s not set	continuous	two driving cycles
Intake Air Temperatur Sensor	P0110	range check high range check low	temperature	> 139,50°C < -42,75°C	only for low: time after start time in idle	> 180s > 10 s	continuous	two driving cycles
Coolant Temperatur Sensor	P0115	range check high	temperature	> 139,50°C	no	-	continuous	two driving cycles
	P0116	range check low rationality	or temperature for closed loop control not reached after time	< -42,75°C <model temp. -12°K timer depending on airflow	engine speed	> 20 rpm		
Throttle Position Sensor	P0120	range check poti voltage, plausibility of poti 1 and poti 2	plausibility of poti 1 and poti 2	> 6,275 %	battery voltage time	> 7 V > 140 ms	continuous	two driving cycles
O2 Sensors								
Front Bank 1 Front Bank 2	P0130 P0150	circuit continuity	sensor signal voltage for time or sensor signal value for time or sensor signal value for time or sensor signal value for time	> 4,7V > 0,2s 0,996<...<1,004 >4...18 s > 1,2 >4...18 s < 0,8 >4...18 s	none either one errorflag: front sensorheater, rear sensor, rear sensor aging indicator self adjust rear sensor voltage rear sensor voltage errorflags: rear sensor, rear sensor aging rear sensor voltage errorflags: rear sensor, rear sensor aging	not present not present > 0,65 V or < 0,30 V > 0,65 V not present < 0,3 V not present	continuous	two driving cycles
Front Bank 1 Front Bank 2	P0131 P0151	range check low	standardized dynamic value from sensor	< 0,60	load engine speed lambdavalue either one errorflag: misfire, evapsystem, purge valve, fueltrim	20,25 <.... < 40,5 % 1400<.... <2400 rpm 0,94 <... <1,06 not present	continuous	two driving cycles

99c30R_V_aE.doc

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					diagnosis secondary air system evapsystem close loop control maximum close loop control minimum	not performed at the moment no high loading indicated not reached or exceeded not reached or exceeded		
Front Bank 1 Front Bank 2	P0132 P0152	range check high	lambda offset	> 0,03	time engine either one errorflag: rear sensor, rear sensor aging rear sensor aging diagnosis	< 2 s running not present finished	continuous	two driving cycles
Front Bank 1 Front Bank 2	P0134 P0154	no activity detected	lambda value	> 0,07	eventcounter timer exhaust model temperatur time after start flag lambda amplitude flag low loadchange flag O2-sensor maxi-mum value exceeded	> 20 > 0,5 s >200 °C >25 s present present not present	continuous	two driving cycles
Heater Front B. 1 Heater Front B. 2	P0135 P0155	range check	heater voltage	> 3,6 V or < 2,34 V	delaytime battery voltage heater outputstage engine	>0,05 s 11,03 <... < 15,52 V active running	continuous	two driving cycles
Rear Bank 1 Rear Bank 2	P0136 P0156	circuit continuity	sensor signal voltage	< 0,04 V	<ul style="list-style-type: none"> • rear close loop • either one errorflag: evapsystem, purge valve • secondary air system • secondary air system diagnosis • flag leakage air through secondary air system • timer • timer • flag tank empty • engine • catalytic converter temperature • battery voltage • lambda target 	established not present not running not running not present > 60 or 80 s > 600 s not present running < 800 °C >11,03 V =1	continuous	two driving cycles

99c30R_V_aE.doc

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Rear Bank 1 Rear Bank 2	P0138 P0158	range check high	sensor signal voltage for time	> 1,08 V 5,1 s	<ul style="list-style-type: none"> • time after dewpoint • engine • catalytic converter temperature • battery voltage • lambda target value • time after dewpoint 	<ul style="list-style-type: none"> > 80 s running < 800 °C > 11,03 V =1 > 80 s 	continuous	two driving cycles
Rear Bank 1 Rear Bank 2	P0140 P0160	no activity detected	sensor signal voltage for time	0,401 <... < 0,519 V 60 s or 600 s	<ul style="list-style-type: none"> • engine • catalytic converter temperature • battery voltage • lambda target value • time after dewpoint 	<ul style="list-style-type: none"> running < 800 °C > 11,03 V =1 > 80 s 	continuous	two driving cycles
Heater Rear B. 1 Heater Rear B. 2	P0141 P0161	heater resistance	actual heater resistance	> Map KFRINH * 5...12	<ul style="list-style-type: none"> • catalytic converter temperature • battery voltage • error flag heater output stage • dewpoint behind catalytic converter • timer 	<ul style="list-style-type: none"> 200 <... < 600°C 11,03 <... < 15,52 V not present reached 	continuous	two driving cycles
Fuel System B. 1 Bank 1 Bank 2 Bank 2	P0171 P0172 P0174 P0175	fuel trim limits exceeded	additional or multiplicational	> 8,5 % or > 23 % < -8,5 % or < -23% > 8,5 % or > 23 % < -8,5 % or < -23 %	<ul style="list-style-type: none"> • fuel system status • fuel trim adaption 	closed loop activ	continuous	two driving cycles
Injection Valve	P0201 to P0206	range check high range check low open circuit	voltage	IC Internal	<ul style="list-style-type: none"> • engine speed • battery voltage • battery voltage • time • stage had to be 	<ul style="list-style-type: none"> > 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active 	continuous	two driving cycles
Fuel Pump Primary Circuit	P0230	range check high range check low open circuit	voltage	IC Internal	<ul style="list-style-type: none"> • engine speed • battery voltage • battery voltage • time • stage had to be 	<ul style="list-style-type: none"> > 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active 	continuous	two driving cycles
Misfire	P0301 to P0306 P0300	crankshaft speed fluctuation cylinder 1 to cylinder 6 Multiple misfire	FTP emission threshold	> 1,07 %	<ul style="list-style-type: none"> • engine speed • load • engine speed change • load change • intake air temp • time after start • rough road • traction control 	<ul style="list-style-type: none"> 520 ... 6520 rpm > RLSALUN (14,25 ... 33 %) < 4000 rpm/s < 250 %/segment >-8,25°C > 5s not detected off 	1000 revs continuous	two driving cycles

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
			catalyst damage	misfire weighted with map rpm/load KFKSWF (4 ... 110) > 600	<ul style="list-style-type: none"> • evap-system check • either one errorflag: throttle position, crankshaft sensor, reference mark sensor 	off not set	200 revs	immediate
Knock Sensor 1 Knock Sensor 2	P0325 P0330	range check low range check high	voltage	table UDKSNU table UDKSNO	<ul style="list-style-type: none"> • coolant temp. • engine speed 	> 39,75°C > 2000 rpm	continuous	no
Crankshaft Position Sensor	P0335	malfunction	counter schedule of phase signal and no signal from crankshaft position sensor	> 8	<ul style="list-style-type: none"> • camshaft signal 	active	continuous	two driving cycles
Camshaft Position Sensor	P0340 P0341	check low/high rationality	bit pattern at crankshaft marker high or low marker not plausible	= 5 times	<ul style="list-style-type: none"> • engine speed 	> 20 rpm	continuous	two driving cycles
Secondary Air System	P0411	flow	relative secondary air mass or relative secondary air mass without offset and secondary air mass offset value	0,25 <...< 0,601 < 0,101 for t > 5 s and > 5,2 kg/h	<ul style="list-style-type: none"> • either one errorflag: coolant-, intakeair-temperature, outputstage secondary airpump, - secondary air valve, evap system, outputstage pruge valve, front O2 sensors, misfire, fueltrim • intake air temperature • airmass integral from catalytic converter heating • catalytic converter temperatur • coolant temperature • altitude factor • engine rpm • airmassflow since start • secondary air system • intake air mass • and 	not present 5,25 <.... < 40,5 °C > 0,5 < 800 °C 18,75 <... < 105 °C > 0,75 running > 0 kg active 10 <... < 90 kg/h or 4 <... < 24 kg/h or 10 <... < 140 kg/h and	ones per trip	two driving cycles

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					• speed for the last two parameters	= 0 km/h		
Secondary Air Valve	P0417	range check high range check low open circuit	voltage	IC Internal	• engine speed • battery voltage • battery voltage • time • stage had to be	> 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active	continuous	two driving cycles
Secondary Air Pump Primary Circuit	P0418	range check high range check low open circuit	voltage	IC Internal	• engine speed • battery voltage • battery voltage • time • stage had to be	> 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active	continuous	two driving cycles
Catalyst, Bank 1 Catalyst, Bank 2	P0422 P0432	determining the oxygen storage capability by comparing the amplitude obtained from the downstream O2-sensor to a modelled sensor-signal amplitude	catalyst quality factor	> 0,65	• engine speed • load • fuel system status • modelled catalyst temp. • modelled signal amplitude • catalyst load value • canister purge value • either one errorflag: O2-sensor upstream and downstream, misfire, air flow sensor, throttle pos. sensor, purge system, fuel system	>1400rpm; < 2200rpm > 25 .. 30 %; < 35 .. 50 % closed loop > 380 °C > 0.25 < 6 .. 8 /s < 8 not present	75 s, once per driving cycle, in case of a fault detection one repeated test possible	two driving cycles
Evaporative Emission Control System	P0440	pressure control	tank pressure while compensation gradient measurement or tank pressure after large leak detection or tank pressure while opening purge solenoid or tank pressure for time period	< - 1,61 hPa < - 14,95 hPa < - 8 hPa - 14 hPa 15 s	• vehicle speed • engine status • fuel system status • canister load factor • tank pressure • engine load • intake low pressure • engine temperature at start • intake air temperature • tank pressure while compensation gradient measurement • battery voltage • time after start	= 0 mph idle closed loop < 8 < 7,82 hPa < 30 % > 450 hPa - 8,25 °C < ... < 75 °C - 8,25 °C < ... < 50,25 °C < 0,25 hPa > 11,03 V > 990 s or fuel mixture adaption OK (b_gae =1) < 2750 m	max.40 s if OK once per driving cycle max. 2 times per driving cycle	two driving cycles

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					<ul style="list-style-type: none"> • altitude • tank pressure while driving cycle • secondary air • secondary air diagnosis • either one errorflag: load-, electr. throttle potentiometer-, coolanttemp.-, vehicle speed-, tank pressure-, oxygensensor, idle control, purge valve -, vent control output stage, battery voltage, misfire 	<p>< 20 hPa inavtive inactive not present</p>		
Evaporative Emission Control System Leak Detected (small leak)	P0442	pressure control	leak air flow volume	table VLTEDFH	<ul style="list-style-type: none"> • vehicle speed • engine status • fuel system status • canister load factor • tank pressure • engine load • intake low pressure • engine temperature at start intake air temperature • tank pressure while compensation gradient • measurement battery voltage • time after start • altitude • tank pressure while driving cycle • secondary air • secondary air diagnosis • either one errorflag: load-, electr. throttle potentiometer-, coolanttemp.-, vehicle speed-, tank pressure-, oxygensensor, idle control, purge valve -, vent control output stage, battery voltage, misfire 	<p>= 0 mph idle closed loop < 8 < 7,82 hPa < 30 % > 450 hPa - 8,25 °C < ... < 75 °C - 8,25 °C < ... < 50,25 °C < 0,25 hPa > 11,03 V > 990 s or fuel mixture adaption OK (b_gae =1) < 2750 m < 20 hPa inactive inactive not present</p>	max.40 s if OK once per driving cycle max. 2 times per driving cycle	two driving cycles

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					stage, battery voltage, misfire			
Evaporative Emission Control System Purge Control Valve Circuit	P0443	range check high range check low open circuit	voltage	IC Internal	<ul style="list-style-type: none"> • engine speed • battery voltage • battery voltage • time • stage had to be 	<ul style="list-style-type: none"> > 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active 	continuous	two driving cycles
Evaporative Emission Control System Vent Control Malfunction	P0446	range check high range check low open circuit	voltage	IC Internal	<ul style="list-style-type: none"> • engine speed • battery voltage • battery voltage • time • stage had to be 	<ul style="list-style-type: none"> > 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active 	continuous	two driving cycles
Evaporative Emission Control System Pressure Sensor	P0450	range check low range check high	sensor signal value sensor signal value or sensor signal value	<ul style="list-style-type: none"> < - 29,375 hPa > 30 hPa <= 25 hPa 	<ul style="list-style-type: none"> • time • time • time • engine status • engine temperature at start time after start 	<ul style="list-style-type: none"> > 5 s > 5 s > 3 s idle <= 33 °C 2 s < ... < 10 s 	max. 10 s	two driving cycles
Evaporative Control System Leak Detected (large leak)	P0455	pressure control or	time for large leak detection no pressure change for	<ul style="list-style-type: none"> > 12,5 s > 4 s 	<ul style="list-style-type: none"> • vehicle speed • engine status • fuel system status • canister load factor • tank pressure • engine load • intake low pressure • engine temperature at start intake air temperature • tank pressure while compensation gradient • measurement battery voltage • time after start • altitude • tank pressure while driving cycle • secondary air • secondary air diagnosis • either one errorflag: load-, electr. throttle potentiometer-, 	<ul style="list-style-type: none"> = 0 mph idle closed loop < 8 < 7,82 hPa < 30 % > 450 hPa - 8,25 °C < ... < 75 °C - 8,25 °C < ... < 50,25 °C < 0,25 hPa > 11,03 V > 990 s or fuel mixture adaption OK (b_gae =1) < 2750 m < 20 hPa inactive inactive not present 	max.40 s if OK once per driving cycle max. 2 times per driving cycle	two driving cycles

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					coolanttemp.-, vehicle speed-, tank pressure-, oxygensensor, idle control, purge valve -, vent control output stage, battery voltage, misfire			
Fuel Level Sensor Circuit	P0460	range check high range check low	Voltage	> 4,8 V < 0,19 V	• time	1 s	continuous	two driving cycles
Vehicle Speed Sensor	P0500	rationality	speed	< 20 km/h	• fuel cut off • engine coolant temperatur • engine speed • time	active > 64,5 °C 1800 <...< 2200 rpm > 1 s	continuous	two driving cycles
Idle Control	P0506 P0507	functional check	actual desired rpm or fuel cuts off during this idle	> 100 rpm < -200 rpm > 3 only for: < -200 rpm	• coolant temp. • intake air temp • vehicle speed • evap (high canister load) • evap diagnostic • secondary air diagnostic • either one errorflag: throttle position, vehicle speed, coolant temp. sensor, intake air sen., evap system, evap valve • load	> 80,25°C > 20,25°C = 0 km/h off off off not set < 30 %	continuous	two driving cycles
System Voltage	P0560	range check high range check low rationality	voltage	> 17 V < 10 V < 2,5 V	• time • vehicle speed • time after start	200ms > 0 km/h 180 s	continuous	two driving cycles
Brake Switches	P0571	plausibility of brake light switch (BLS) and brake test switch (BTS)	several times BLS and BTS unplausible for a certain period	> 1 s > 10 times	• no	-	continuous	no
Calculator Monitoring	P0601	ROM Check	check sum ROM error		• no		continuous	two driving cycles
ECM	P0602	Programming Error	Security Access not armed		• no		at enginestart	no
Calculator Monitoring	P0603	Calculator check	Calculator Check		• no		continuous	two driving cycles
Calculator Monitoring	P0604	RAM check	Read- and write-Test		• no		continuous	two driving

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
								cycles
Function Monitoring	P0606	monitoring torque safety fuel cut off	torque out of range calculator error in function		• engine speed	> 1120 rpm	continuous	two driving cycles
MIL	P0650	range check high range check low open circuit	voltage	IC Internal	• engine speed • battery voltage • battery voltage • time • stage had to be	> 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active	continuous	two driving cycles
Intake Air Throttle Charge Over 1 Charge Over 2	P1112 P1113	range check high range check low open circuit	voltage	IC Internal	• engine speed • battery voltage • battery voltage • time • stage had to be	> 40 rpm > 7,5 V < 15 V 300 ms ... 500 ms active	continuous	two driving cycles
Throttle Position Sensor 1	P1120	range check high range check low rationality	voltage plausibility to airmass flow in case of deviation from poti 2	> 4,6 V < 0,195 V > 12,9 %	• time • battery voltage	> 140ms > 7 V	continuous	two driving cycles
Accelerator Pedal Position Sensor	P1125	range check poti, plausibility to other poti	see error accelerator pedal position sensor 1 and sensor 2	-	• battery voltage	> 7 V	continuous	no
Outputstage O2 Heater Rear B. 1 Heater Rear B. 2	P1141 P1161	circuit continuity	voltage	IC internal	• stage had to be • battery voltage	active > 9 V	continuous	two driving cycles
Throttle Position Sensor 2	P1220	range check high range check low rationality	voltage plausibility to airmass flow in case of deviation from poti 1	> 4,8 V < 0,156 V > 12,9 %	• time • battery voltage	> 140ms > 7 V	continuous	two driving cycles
Accelerator Pedal Position Sensor Pedal Moving Detection	P1271	comparison of poti 1 and poti 2 when leaving idle range	voltage	> 0,8789 V < 0,6836 V	• battery voltage • no substitute operation of accelerator pedal position sensor	> 7 V	continuous	no
Accelerator Pedal Position Sensor 1	P1275	range check high range check low plausibility to poti 2	voltage volt. part. throttle range volt. full throttle range	> 4,3359 V < 0,2344 V > 0,2734 V > 1,1328 V	• battery voltage	> 7 V	continuous	no
Accelerator Pedal Position Sensor 2	P1280	range check high range check low plausibility to poti 1	voltage volt. part. throttle range volt. full throttle range	>> 4,8828 V < 0,1172 V > 0,2734 V > 1,1328 V	• battery voltage	> 7 V	continuous	no
Misfire With Low	P1460	Fuel Level	Liter	< 11 l	• time	30 s	continuous	no

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Fuel					or • Misfire detected or • fuel trim limits exceeded	yes		
Immobilizer	P1501 P1502 P1503	rationality	not or wrong initialized no frequencycode received wrong frequencycode received		• at cranking			no
DV-E Control Range	P1510	range check high range check low	PWM time	> 80 % > 80 % PWM for time > 0,6 s (first threshold) or > 5 s (second threshold)	• battery voltage • status DVE-E adaption	> 7 V not set	continuous	two driving cycles
DV-E Limp-Home Air Position	P1511	check of limp-home air position	throttle position	< 3,16 % > 10,46 %	• vehicle speed • engine speed • coolant temp. • intake air temp. • battery voltage • pedal position	= 0 km/h < 250 rpm 5°C <... < 100°C > 5°C > 10 V < 15 %	continuous	two driving cycles
DV-E Position Throttle Blade	P1516	difference between set and actual position of throttle blade	difference value	> DWDKSBAMX for time > 0,5 s	• status DVE-E adaption	not set	continuous	two driving cycles
DV-E Power Stage Switch Off	P1519	output	state	not set for time > 5 s	• status DVE-E adaption • duty cycle range check	not set > 80 % PWM	continuous	two driving cycles
DV-E Spring Check	P1523	check of DV-E return spring	active opening throttle blade, switch off power stage and monitoring the throttle blade return	> (angle limp-home + 3%) for time > 0,56 s	• vehicle speed • engine speed • coolant temp. • intake air temp.	= 0 km/h < 250 rpm 5°C <... < 100°C > 5°C	once per DV-E adap.	two driving cycles
DV-E Lower Mechanical Stop Throttle Blade	P1526	range check lower mechanical stop throttle blade	range check high range check low	< 0,24 V > 0,80 V < 4,20V > 4,77V	• vehicle speed • engine speed • coolant temp. • intake air temp. • battery voltage • pedal position	= 0 km/h < 250 rpm 5°C <... < 100°C > 5°C > 10 V < 15 %	once per DV-E adap.	two driving cycles
DV-E Amplifier Adjustment	P1530	range check of amplified actual throttle blade position signal	amplification value offset value	< 4,00 V > 4,32 V < -0,055 V > 0,055 V	• vehicle speed • engine speed • coolant temp. • intake air temp. • battery voltage • pedal position	= 0 km/h < 250 rpm 5°C <... < 100°C > 5°C > 10 V < 15 %	once per DV-E adap.	two driving cycles
Knock Control	P1602	rationality	IC output voltage	>44,983 V/s	• coolant temp. (knock)	> 39,75°C	continuous	no

99c30R_V_aE.doc

1999 3.0L (L81) V-car Catera ENGINE DIAGNOSTIC PARAMETERS

99c30R_V_aE.doc

Component / System	Fault	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Module				> 0,2148 V < 3,6914 V	control active)			
Transmission MIL Request	P1700	TCM	OBD2 failure				continuous	immediately
CAN-BUS Communication Malfunction	U2100	CAN-BUS circuit	Common not identified bus error		• engine speed • time	> 25 U/min > 25 sec	continuous	no
CAN-BUS Fewer Controller On Bus Than Controlled	U2102	CAN-BUS circuit	Fewer systems on bus than programmed in the maximum configuration list	< 3	• engine speed • time	> 25 U/min > 25 sec	continuous	two driving cycles
CAN-BUS Reset Counter Overrun	U2104	CAN-BUS circuit	Reset Counter	> 40	• engine speed • time	> 25 U/min > 25 sec	continuous	two driving cycles
CAN-BUS Lost Communication With TCM	U2106	CAN-BUS circuit	No communication with TCM		• engine speed • time	> 25 U/min > 25 sec	continuous	two driving cycles
CAN-BUS Lost Communication With ABS	U2108	CAN-BUS circuit	No communication with ABS		• engine speed • time	> 25 U/min > 25 sec	continuous	two driving cycles