

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Mass Air Flow Sensor Circuit - Range/Rationality	P0101	0 kHz - 13 kHz Under conditions when the two should match, the Mass Air Flow reading should match calculated Mass Air Flow (based on speed density. If delta Mass Air Flow is too large, a faulty Mass Air Flow condition exists, such as a "skewed" sensor.	MAF $\Delta \geq$ a table value determined by the difference between the MAF sensor reading and the speed density calculation.	Engine Running TP sensor DTC's not active. MAP sensor DTC's not active. Evap. DTC's not active EGR DTC P0401 not active MAF sensor high / low DTC's not active. Crank Sensor DTC's not active IAT Sensor DTC's not active System voltage > 11V but < 16V Canister Purge DC \leq 99.6% TP $\Delta \leq$ 3.9% EGR DC \leq 89.8% EGR Pintle Position \leq 89.8% Engine vacuum \leq 75 kPa Throttle Position \leq 89.8% The above must be present for a period of time greater than 2 seconds.	50 test failures within a 100 test sample. Time necessary to complete sample: 10 sec The Mass Air Flow reading and Mass Air Flow calculation are performed during the same cylinder event every 100 ms.	DTC Type B
Mass Air Flow Sensor Circuit - Low Input	P0102	0kHz - 13 kHz This DTC will determine if the MAF frequency is too low.	<u>LOW FREQUENCY TEST:</u> MAF \leq 10 Hz	<u>LOW FREQUENCY TEST:</u> Engine Running Engine Run Time \geq 0.4 seconds Engine Speed \geq 300 RPM System Voltage \geq 8 Volts The above must be present for a period of time greater than 0 seconds.	<u>LOW FREQUENCY TEST:</u> 4 test failures within a 16 test sample. Time necessary to complete sample: 1 sec at 500 RPM Test is run at every reading of the Mass Air Flow sensor frequency.	DTC Type B
Mass Air Flow Sensor Circuit - High Input	P0103	0kHz - 13 kHz This DTC will determine if the MAF frequency is too high	<u>HIGH FREQUENCY TEST:</u> MAF \geq 11000 Hz	<u>HIGH FREQUENCY TEST:</u> Engine Running Engine Run Time \geq 0.4 seconds Engine Speed \geq 300 RPM System Voltage \geq 8 Volts The above must be present for a period of time greater than 0 seconds.	<u>HIGH FREQUENCY TEST:</u> 6 test failures within a 16 test sample. Time necessary to complete sample: 1 sec at 500 RPM Test is run at every reading of the Mass Air Flow sensor frequency.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
MAP Sensor - Range/Rationality	P0106	.3V to 5.0V Under proper conditions, the MAP value should be within a window (based on throttle position and engine speed). If not, a faulty MAP condition such as a "skewed" sensor exists.	A table defining the minimum acceptable MAP value \leq MAP \leq a table defining the maximum acceptable MAP value	TP sensor DTC's not active Engine Running Engine Speed Δ < 75 RPM Throttle Position Δ < 1.5% Idle Air Δ < 4 steps EGR Flow Rate Δ < 2% Brake Switch State = no change Clutch Switch State = no change AC Clutch State = no change Above stabilized for 2 seconds EGR DTC's not active Engine Speed \geq 400 RPM Engine Speed \leq 5000 RPM	24 test failures within a 100 test sample. Time necessary to complete sample: 100 sec Continuous	DTC Type B
MAP Sensor Circuit - Low Input	P0107	.3V to 5.0V This DTC detects a continuous short to low or open in either the signal circuit or the MAP sensor.	Raw MAP < 0.04 Volts (3 counts)	TP sensor DTC's not active Engine Running Throttle Position \geq 0% when Engine speed is \leq 800 RPM or Throttle Position is \geq 12.5% when Engine speed is > 800 RPM	40 test failures within a 100 test sample. Time necessary to complete sample is based on engine speed. At 1600 RPM, the time would be 1 sec. Continuous	DTC Type B
MAP Sensor Circuit - High Input	P0108	.3V to 5.0V This DTC detects an open sensor ground or continuous short to high in either the signal circuit or the MAP sensor.	Raw MAP > 4.4 Volts (222 counts)	Cold Start Run Time - Table value in seconds based on Powerup Coolant Temperature. Run Test TP sensor DTC's not active Throttle Position \leq 0.4% when Engine speed is \leq 1200 RPM or Throttle Position is \leq 20 % when Engine speed is > 1200 RPM	40 test failures within a 100 test sample. Time necessary to complete sample is based on engine speed. At 1600 RPM, the time would be 1 sec. Continuous	DTC Type B
Intake Air Temp. Sensor Circuit -Low Input	P0112	.24V to 5.0V The DTC detects a continuous short to ground in the IAT signal circuit or the IAT sensor	Low Resistance pull-up Raw IAT < 0.82 Volts High Resistance pull-up Raw IAT < 0.07 Volts	VS sensor DTC's not active Vehicle speed \geq 2 mph Engine run time > 100 seconds	40 test failures within a 100 test sample Time necessary to complete sample: 12.5 sec Continuous	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Intake Air Temp. Sensor Circuit - High Input	P0113	.24V to 5.0V The DTC detects a continuous open or short to high in the IAT signal circuit or the IAT sensor	<u>Low Resistance pull-up</u> Raw IAT > 4.9 Volts <u>High Resistance pull-up</u> Raw IAT > 4.9 Volts	ECT sensor DTC's not active VS sensor DTC's not active MAF sensor DTC's not active Vehicle speed < 2 mph Mass Air flow < 250 g/s Coolant Temperature > 84.7°C Engine run time > 100 seconds	40 test failures within a 100 test sample Time necessary to complete sample: 12.5 sec Continuous	DTC Type B
Engine Coolant Temp. Sensor Circuit-Low Input	P0117	.24V to 5.0V The DTC detects a continuous short to ground in the ECT signal circuit or the ECT sensor	<u>Low Resistance pull-up</u> Raw ECT < 0.25 Volts <u>High Resistance pull-up</u> Raw ECT < 0.25 Volts	Engine run time > 5 seconds	40 test failures within a 100 test sample Time necessary to complete sample: 50 sec Continuous	DTC Type B
Engine Coolant Temp. Sensor Circuit-High Input	P0118	.24V to 5.0V The DTC detects a continuous short to high or open in the ECT signal circuit or the ECT sensor	<u>Low Resistance pull-up</u> Raw ECT > 4.9 Volts <u>High Resistance pull-up</u> Raw ECT > 4.9 Volts	Engine run time > 5 seconds	40 test failures within a 100 test sample Time necessary to complete sample: 50 sec Continuous	DTC Type B
Throttle Position Sensor Circuit-Range/Rationality	P0121	.5V to 5.0V The DTC detects a "skewed" or stuck TP sensor	<u>Stuck high test:</u> The last throttle position value is > predicted throttle position based on engine RPM. <u>Stuck low test:</u> The last throttle position value is < predicted throttle position based on engine RPM.	<u>Test Enable:</u> No TP sensor short DTC's active No IAC DTC's active No MAP DTC's active Engine running BARO not defaulted TP Δ < 1.9% <u>Stuck high test:</u> MAP < 50 kPa <u>Stuck low test:</u> Stuck high test has passed MAP > 65 kPa IAC > 10 counts but < 340 counts	<u>Stuck high test:</u> 50 test failures within a 100 test sample <u>Stuck low test:</u> 50 test failures within a 100 test sample Time necessary to complete each sample: 10 sec Continuous	DTC Type B
Throttle Position Sensor Circuit-Low Input	P0122	.5V to 5.0V This DTC detects a continuous short to low or open in either the signal circuit or the TP sensor.	TP sensor signal voltage < 0.25 volts (13 counts)	Engine running	5 consecutive test failures within a 10 test sample Time necessary to complete sample: 1 sec Continuous	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit-Low Voltage (Bank 1, Sensor 1)	P0131	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to low by checking for a lean condition during steady state throttle and during power enrichment (PE).	<u>Lean test:</u> O2 sensor voltage < 86 mV or <u>PE Lean Test:</u> O2 sensor voltage < 598 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 lean tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Lean test):</u> Closed loop low MAP not active Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 3.5% but < 99% Above met for 5 seconds <u>Test Enable (PE Lean test):</u> Closed loop Power Enrichment mode active High speed fuel cutoff not active Time elapsed since test enable ≥ 1 sec.	<u>Lean Test:</u> 500 test failures in a 600 test sample Time necessary to complete sample: 60 sec Continuous or <u>PE Lean Test:</u> 300 test failures in a 500 test sample. Time necessary to complete sample: 50 sec	DTC Type B
O2S Circuit-High Voltage (Bank 1, Sensor 1)	P0132	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to high by checking for a rich condition during steady throttle and Decel fuel cutoff (DFCO)	<u>RichTest:</u> O2 sensor voltage > 976 mV or <u>DFCO Rich Test:</u> O2 sensor voltage > 468 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 rich tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Rich Test):</u> Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 0% but < 50% Above met for 5 seconds <u>Test Enable (DFCO Rich Test):</u> Decel Fuel Cutoff mode active Closed loop Time elapsed since test enable ≥ 2 sec.	<u>Rich Test:</u> 400 test failures in a 500 test sample Time necessary to complete sample: 50 sec Continuous or <u>DFCO Rich Test:</u> 300 test failures in a 500 test sample Time necessary to complete sample: 50 sec	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit-Slow Response (Bank 1, Sensor 1)	P0133	.1V to 1.0V This DTC determines if the O2 sensor functioning properly by checking its response time.	O2 sensor average transition time: L/R > 125 milliseconds R/L > 125 milliseconds *O2 voltage < 300 mV = lean *O2 voltage > 600 mV = rich	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 Response tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 9 Volts <u>Response Test Enable:</u> 11.7 but <18 Volts Closed loop low MAP not active DTC's P0131, P0132, P0134 and P0135 not active Closed loop ECT > 57°C Engine run time > 75 seconds Air flow ≥ 15 g/s but ≤ 55 g/s Engine speed ≥ 1100 rpm but ≤ 3000 rpm Canister Purge Duty Cycle ≥ 0% Above present for > 2 seconds	100 seconds after closed loop enable Once per ignition cycle	DTC Type B
O2S Circuit- No Activity Detected (Bank 1, Sensor 1)	P0134	.1V to 1.0V This DTC determines if the O2 sensor or the O2 sensor circuit has developed an open.	O2 sensor > 300 mV but < 600 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 open test) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts Engine Run Time ≥ 120 seconds <u>O2 Sensor Temperature Test:</u> Not in DFCO ECT ≥ 58.5°C Air Flow ≥ 13 g/s <u>O2 sensor Open test enable:</u> O2 Sensor Temperature Test = True DTC P0135 not active Closed Loop	800 test failures with in a 1000 test sample Time necessary to complete sample: 100 sec Continuous	DTC Type B
O2S Heater Circuit Malfunction (Bank 1, Sensor 1)	P0135	11.7 to 18 Volts This DTC determines if the O2 sensor heater is functioning properly by monitoring the amount of time necessary for the O2 sensor to become active after start - up.	The elapsed time to obtain ± .150V from the mean O2 bias voltage. *Time based on table: Time Vs Average Air Flow	System Voltage > 11.7 but <18 Volts (NOTE: If voltage remains outside this window for 4 consecutive seconds, the test is void for this cold start.) Air Flow < 27 g/sec (21 g/s 4.3L M/L only - Denso Sensors; 35 g/s - 5.7L only) Engine run time > 2 seconds ECT < 33°C IAT < 33°C Δ ECT-IAT ≤ 5°C	From cold start to a maximum time of 130 seconds. *Time determined by table.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit-Low Voltage (Bank 1, Sensor 2) ⑤⑥⑦⑧⑨	P0137	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to low by checking for a lean condition during steady state throttle and during power enrichment (PE).	<p><u>Lean test:</u> O2 sensor voltage < 26 mV</p> <p>or</p> <p><u>PE Lean Test:</u> O2 sensor voltage < 399 mV</p>	<p><u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 lean tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Lean test):</u> Closed loop low MAP not active Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 3.5% but < 99% Above met for 5 seconds <u>Test Enable (PE Lean test):</u> Closed loop Power Enrichment mode active High speed fuel cutoff not active Time elapsed since test enable ≥ 2 sec.</p>	<p><u>Lean Test:</u> 1100 test failures in a 1300 test sample</p> <p>Time necessary to complete sample: 130 sec</p> <p>Continuous</p> <p>or</p> <p><u>PE Lean Test:</u> 400 test failures in a 500 test sample.</p> <p>Time necessary to complete sample: 50 sec</p>	DTC Type B
O2S Circuit-High Voltage (Bank 1, Sensor 2) ⑤⑥⑦⑧⑨	P0138	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to high by checking for a rich condition during steady throttle and Decel fuel cutoff (DFCO)	<p><u>RichTest:</u> O2 sensor voltage > 994mV</p> <p>or</p> <p><u>DFCO Rich Test:</u> O2 sensor voltage > 469 mV</p>	<p><u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 rich tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Rich Test):</u> Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 0% but < 50% Above met for 5 seconds <u>Test Enable (DFCO Rich Test):</u> Decel Fuel Cutoff mode active Closed loop Time elapsed since test enable ≥ 2 sec.</p>	<p><u>Rich Test:</u> 1100 test failures in a 1500 test sample</p> <p>Time necessary to complete sample: 150 sec</p> <p>Continuous</p> <p>or</p> <p><u>DFCO Rich Test:</u> 400 test failures in a 500 test sample</p> <p>Time necessary to complete sample: 50 sec</p>	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit- No Activity Detected (Bank 1, Sensor 2) ⑤⑥⑦⑧⑨	P0140	.1V to 1.0V This DTC determines if the O2 sensor or the O2 sensor circuit has developed an open.	O2 sensor > 400 mV but < 473 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 open test) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts Engine Run Time ≥ 120 seconds <u>O2 Sensor Temperature Test:</u> Not in DFCO ECT ≥ 58.5°C Air Flow ≥ 13 g/s <u>O2 sensor Open test enable:</u> O2 Sensor Temperature Test = True DTC P0141 not active Closed Loop	1000 test failures with in a 1200 test sample Time necessary to complete sample: 120 sec Continuous	DTC Type B
O2S Heater Circuit Malfunction (Bank 1, Sensor 2) ⑤⑥⑦⑧⑨	P0141	11.7 to 18 Volts This DTC determines if the O2 sensor heater is functioning properly by monitoring the amount of time necessary for the O2 sensor to become active after start - up.	The elapsed time to obtain ± .150V from the mean O2 bias voltage. *Time based on table: Time Vs Average Air Flow	System Voltage > 11.7 but <18 Volts (NOTE: If voltage remains outside this window for 4 consecutive seconds, the test is void for this cold start.) Air Flow < 35 g/sec (27 g/s 4.3L GMT800) Engine run time > 2 seconds ECT < 33°C IAT < 33°C Δ ECT-IAT ≤ 5°C	From cold start to a maximum time of 245 seconds. *Time determined by table.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit-Low Voltage (Bank 1, Sensor 3) ①②③④	P0143	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to low by checking for a lean condition during steady state throttle and during power enrichment (PE).	<p><u>Lean test:</u> O2 sensor voltage < 26 mV</p> <p>or</p> <p><u>PE Lean Test:</u> O2 sensor voltage < 399 mV</p>	<p><u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 lean tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Lean test):</u> Closed loop low MAP not active Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 3.5% but < 99% Above met for 5 seconds</p> <p><u>Test Enable (PE Lean test):</u> Closed loop Power Enrichment mode active High speed fuel cutoff not active Time elapsed since test enable ≥ 2 sec.</p>	<p><u>Lean Test:</u> 1100 test failures in a 1300 test sample</p> <p>Time necessary to complete sample: 130 sec</p> <p>Continuous</p> <p>or</p> <p><u>PE Lean Test:</u> 400 test failures in a 500 test sample.</p> <p>Time necessary to complete sample: 50 sec</p>	DTC Type B
O2S Circuit-High Voltage (Bank 1, Sensor 3) ①②③④	P0144	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to high by checking for a rich condition during steady throttle and Decel fuel cutoff (DFCO)	<p><u>RichTest:</u> O2 sensor voltage > 994mV</p> <p>or</p> <p><u>DFCO Rich Test:</u> O2 sensor voltage > 469 mV</p>	<p><u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 rich tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Rich Test):</u> Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 0% but < 50% Above met for 5 seconds <u>Test Enable (DFCO Rich Test):</u> Decel Fuel Cutoff mode active Closed loop Time elapsed since test enable ≥ 2 sec.</p>	<p><u>Rich Test:</u> 1100 test failures in a 1500 test sample</p> <p>Time necessary to complete sample: 150 sec</p> <p>Continuous</p> <p>or</p> <p><u>DFCO Rich Test:</u> 400 test failures in a 500 test sample</p> <p>Time necessary to complete sample: 50 sec</p>	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit- No Activity Detected (Bank 1, Sensor 3) ①②③④	P0146	.1V to 1.0V This DTC determines if the O2 sensor or the O2 sensor circuit has developed an open.	O2 sensor > 399 mV but < 473 mV	<p><u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 open test) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts Engine Run Time ≥ 120 seconds <u>O2 Sensor Temperature Test:</u> Not in DFCO ECT ≥ 58.5°C Air Flow ≥ 13 g/s <u>O2 sensor Open test enable:</u> O2 Sensor Temperature Test = True DTC P0147 not active Closed Loop</p>	1000 test failures with in a 1200 test sample Time necessary to complete sample: 120 sec Continuous	DTC Type B
O2S Heater Circuit Malfunction (Bank 1, Sensor 3) ①②③④	P0147	11.7 to 18 Volts This DTC determines if the O2 sensor heater is functioning properly by monitoring the amount of time necessary for the O2 sensor to become active after start - up.	The elapsed time to obtain ± .150V from the mean O2 bias voltage. *Time based on table: Time Vs Average Air Flow	System Voltage > 11.7 but <18 Volts NOTE: If voltage remains outside this window for 4 consecutive seconds, the test is void for this cold start.) Air Flow < 27 g/sec (21 g/s 4.3L M/L van only - Denso Sensors) Engine run time > 2 seconds ECT < 33°C IAT < 33°C Δ ECT-IAT ≤ 5°C	From cold start to a maximum time of 245 seconds. (270sec 4.3L M/L van only - Denso Sensors) *Time determined by table.	DTC Type B
O2S Circuit-Low Voltage (Bank 2, Sensor 1)	P0151	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to low by checking for a lean condition during steady state throttle and during power enrichment (PE).	<p><u>Lean test:</u> O2 sensor voltage < 86 mV</p> <p>or</p> <p><u>PE Lean Test:</u> O2 sensor voltage < 598 mV</p>	<p><u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 lean tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Lean test):</u> Closed loop low MAP not active Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 3.5% but < 99% Above met for 5 seconds <u>Test Enable (PE Lean test):</u> Closed loop Power Enrichment mode active High speed fuel cutoff not active Time elapsed since test enable ≥ 1 sec.</p>	<p><u>Lean Test:</u> 500 test failures in a 600 test sample Time necessary to complete sample: 60 sec Continuous or <u>PE Lean Test:</u> 300 test failures in a 500 test sample. Time necessary to complete sample: 50 sec</p>	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit-High Voltage (Bank 2, Sensor 1)	P0152	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to high by checking for a rich condition during steady throttle and Decel fuel cutoff (DFCO)	<u>Rich Test:</u> O2 sensor voltage > 976 mV or <u>DFCO Rich Test:</u> O2 sensor voltage > 468 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 rich tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage \geq 11.7 but <18 Volts <u>Test Enable (Rich Test):</u> Closed loop Air/Fuel ratio \geq 14.5 but \leq 14.8 Throttle position > 0% but < 50% Above met for 5 seconds <u>Test Enable (DFCO Rich Test):</u> Decel Fuel Cutoff mode active Closed loop Time elapsed since test enable \geq 2 sec.	<u>Rich Test:</u> 400 test failures in a 500 test sample Time necessary to complete sample: 50 sec Continuous or <u>DFCO Rich Test:</u> 300 test failures in a 500 test sample Time necessary to complete sample: 50 sec	DTC Type B
O2S Circuit-Slow Response (Bank 2, Sensor 1)	P0153	.1V to 1.0V This DTC determines if the O2 sensor functioning properly by checking its response time.	O2 sensor average transition time: L/R > 125 milliseconds R/L > 125 milliseconds *O2 voltage < 300 mV = lean *O2 voltage > 600 mV = rich	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 Response tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage \geq 11.7 but <18 Volts <u>Response Test Enable:</u> Closed loop low MAP not active DTC's P0151, P0152, P0154 and P0155 not active Closed loop ECT > 57°C Engine run time > 75 seconds Air flow \geq 15 g/s but \leq 55 g/s Engine speed \geq 1100 rpm but \leq 3000 rpm Canister Purge Duty Cycle \geq 0% Above present > 2 seconds	100 seconds after closed loop enable Once per ignition cycle	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit- No Activity Detected (Bank 2, Sensor 1)	P0154	.1V to 1.0V This DTC determines if the O2 sensor or the O2 sensor circuit has developed an open.	O2 sensor > 300 mV but < 600 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 open test) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts Engine Run Time ≥ 120 seconds <u>O2 Sensor Temperature Test:</u> Not in DFCO ECT ≥ 58.5°C Air Flow ≥ 13 g/s <u>O2 sensor Open test enable:</u> O2 Sensor Temperature Test = True DTC P0155 not active Closed Loop	800 test failures with in a 1000 test sample Time necessary to complete sample: 100 sec Continuous	DTC Type B
O2S Heater Circuit Malfunction (Bank 2, Sensor 1)	P0155	11.7 to 18 Volts This DTC determines if the O2 sensor heater is functioning properly by monitoring the amount of time necessary for the O2 sensor to become active after start - up.	The elapsed time to obtain ± .150V from the mean O2 bias voltage. *Time based on table: Time Vs Average Air Flow	System Voltage > 11.7 but <18 Volts (NOTE: If voltage remains outside this window for 4 consecutive seconds, the test is void for this cold start.) Air Flow < 27 g/sec (21 g/s 4.3L M/L only - Denso Sensors; 35 g/s - 5.7L only) Engine run time > 2 seconds ECT < 33°C IAT < 33°C Δ ECT-IAT ≤ 5°C	From cold start to a maximum time of 130 seconds. *Time determined by table.	DTC Type B
O2S Circuit-Low Voltage (Bank 2, Sensor 2) ⑤⑥⑦⑧⑨	P0157	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to low by checking for a lean condition during steady state throttle and during power enrichment (PE).	<u>Lean test:</u> O2 sensor voltage < 26 mV or <u>PE Lean Test:</u> O2 sensor voltage < 399 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 lean tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Lean test):</u> Closed loop low MAP not active Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 3.5% but < 99% Above met for 5 seconds <u>Test Enable (PE Lean test):</u> Closed loop Power Enrichment mode active High speed fuel cutoff not active Time elapsed since test enable ≥ 2sec.	<u>Lean Test:</u> 1100 test failures in a 1300 test sample Time necessary to complete sample: 130 sec Continuous or <u>PE Lean Test:</u> 400 test failures in a 500 test sample. Time necessary to complete sample: 50 sec	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit-High Voltage (Bank 2, Sensor 2) ⑤⑥⑦⑧⑨	P0158	.1V to 1.0V This DTC determines if the O2 sensor or circuit is shorted to high by checking for a rich condition during steady throttle and Decel fuel cutoff (DFCO)	<u>Rich Test:</u> O2 sensor voltage > 994 mV or <u>DFCO Rich Test:</u> O2 sensor voltage > 469 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 rich tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Test Enable (Rich Test):</u> Closed loop Air/Fuel ratio ≥ 14.5 but ≤ 14.8 Throttle position > 0% but < 50% Above met for 5 seconds <u>Test Enable (DFCO Rich Test):</u> Decel Fuel Cutoff mode active Closed loop Time elapsed since test enable ≥ 2 sec.	<u>Rich Test:</u> 1100 test failures in a 1500 test sample Time necessary to complete sample: 150 sec Continuous or <u>DFCO Rich Test:</u> 400 test failures in a 500 test sample Time necessary to complete sample: 50 sec	DTC Type B
O2S Circuit- No Activity Detected (Bank 2, Sensor 2) ⑤⑥⑦⑧⑨	P0160	.1V to 1.0V This DTC determines if the O2 sensor or the O2 sensor circuit has developed an open.	O2 sensor > 399 mV but < 473 mV	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 open test) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts Engine Run Time ≥ 120 seconds <u>O2 Sensor Temperature Test:</u> Engine Running Not in DFCO ECT ≥ 58.5°C Air Flow ≥ 13 g/s <u>O2 Sensor Open Test Enable:</u> O2 Sensor Temperature Test = True DTC P0155 not active Closed Loop	1000 test failures with in a 1200 test sample Time necessary to complete sample: 120 sec Continuous	DTC Type B
O2S Heater Circuit Malfunction (Bank 2, Sensor 2) ⑤⑥⑦⑧⑨	P0161	11.7 to 18 Volts This DTC determines if the O2 sensor heater is functioning properly by monitoring the amount of time necessary for the O2 sensor to become active after start - up.	The elapsed time to obtain ± .150V from the mean O2 bias voltage. *Time based on table: Time Vs Average Air Flow	System Voltage > 11.7 but <18 Volts (NOTE: If voltage remains outside this window for 4 consecutive seconds, the test is void for this cold start.) Air Flow < 35 g/sec (27 g/s 4.3L GMT800) Engine run time > 2 seconds ECT < 33°C IAT < 33°C Δ ECT-IAT ≤ 5°C	From cold start to a maximum time of 245 seconds. *Time determined by table.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
System Too Lean (Bank 1)	P0171	Determines if the system is in a lean condition.	The average of short term fuel trim samples ≥ 1.0 and The average of adaptive index multiplier samples ≥ 1.20	Test Enable: O2 sensor DTC's not active TP sensor DTC's not active MAP DTC's not active EGR DTC's not active Evap. DTC's not active ECT DTC's not active MAF DTC's not active IAT DTC's not active VS sensor DTC's not active Misfire DTC's not active Throttle position < 69.9% Engine speed > 500 rpm but < 4000 rpm Baro > 70 kPa ECT > 75°C but < 114°C MAP > 22 kPa but < 85 kPa IAT > -8.25 °C but < 76°C Air flow > 3 g/s < 85g/s Vehicle speed < 85 mph	If lean counter is ≥ 6 counts 1 count \cong 200 ms Continuous	DTC Type B
System Too Rich (Bank 1)	P0172	Determines if the system is in a rich condition.	The average of short term fuel trim samples ≤ 1.0 and If adaptive lag factor < 0.86, then purge valve is commanded closed. If the integrator exceeds 1.023 or the delta integrator during test exceeds 0.16 within 10 seconds, the diagnostic is turned OFF for 300 seconds to enable the Evap. canister to purge. If the integrator does not exceed 1.023 or the integrator does not change by 0.16 within 10 seconds, a fault is present.	Test Enable: O2 sensor DTC's not active TP sensor DTC's not active MAP DTC's not active EGR DTC's not active Evap. DTC's not active ECT DTC's not active MAF DTC's not active IAT DTC's not active VS sensor DTC's not active Misfire DTC's not active Throttle position < 69.9% Engine speed > 500 rpm but < 4000 rpm Baro > 70 kPa ECT > 75°C but < 114°C MAP > 22 kPa but < 85 kPa IAT > -8.25°C but < 76°C Air flow > 3 g/s < 85g/s Vehicle speed < 85 mph	If rich counter is ≥ 6 counts 1 count \cong 200 ms Continuous	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
System Too Lean (Bank 2)	P0174	Determines if the system is in a lean condition.	The average of short term fuel trim samples ≥ 1.0 and The average of adaptive index multiplier samples ≥ 1.20	Test Enable: O2 sensor DTC's not active TP sensor DTC's not active MAP DTC's not active EGR DTC's not active Evap. DTC's not active ECT DTC's not active MAF DTC's not active IAT DTC's not active VS sensor DTC's not active Misfire DTC's not active Throttle position < 69.9% Engine speed > 500 rpm but < 4000 rpm Baro > 70 kPa ECT > 75°C but < 114°C MAP > 22 kPa but < 85 kPa IAT > -8.25°C but < 76°C Air flow > 3 g/s < 85 g/s Vehicle speed < 85 mph	If lean counter is ≥ 6 counts 1 count \cong 200 ms Continuous	DTC Type B
System Too Rich (Bank 2)	P0175	Determines if the system is in a rich condition.	The average of short term fuel trim samples ≤ 1.0 and If adaptive lag factor < 0.86, then purge valve is commanded closed. If the integrator exceeds 1.023 or the delta integrator during test exceeds 0.16 within 10 seconds, the diagnostic is turned OFF for 300 seconds to enable the Evap. canister to purge. If the integrator does not exceed 1.023 or the integrator does not change by 0.16 within 10 seconds, a fault is present.	Test Enable: O2 sensor DTC's not active TP sensor DTC's not active MAP DTC's not active EGR DTC's not active Evap. DTC's not active ECT DTC's not active MAF DTC's not active IAT DTC's not active VS sensor DTC's not active Misfire DTC's not active Throttle position < 69.9% Engine speed > 500 rpm but < 4000 rpm Baro > 70 kPa ECT > 75°C but < 114°C MAP > 22 kPa but < 85kPa IAT > -8.25 °C but < 76°C Air flow > 3 g/s < 85 g/s Vehicle speed < 85 mph	If rich counter is ≥ 6 counts 1 count \cong 200 ms Continuous	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Random Misfire Detected	P0300	This DTC will determine if a misfire is occurring in one or more cylinders in the engine.	Deceleration index Vs Engine Speed Vs Load and Camshaft Position FTP Threshold - 1.85% I/M Threshold - 1.85% Catalyst Damage - see speed/load chart	<u>TEST Enable:</u> If start up ECT below -7 C then MFD delayed until ECT is above 21 C. If start up ECT \geq is above -7° C then MFT begins after 5 seconds Fuel Level > 10% System voltage \geq 11 volts but \leq 16 volts Engine speed \geq 450 RPM but \leq 5000 RPM Vehicle speed DTC not active TP sensor DTC's not active MAF sensor DTC's not active Camshaft position sensor DTC's not active Crank sensor DTC's not active + Throttle position $\Delta <$ 1.9%/100ms - Throttle position $\Delta <$ 1.9%/100ms	Emission Level 10 failed 200 revolution blocks out of 16 Catalyst Damaging Level 4 failed 200 revolution block out of 16 Continuous	DTC Type B <i>EMISSION</i> DTC Type A <i>CATALYST DAMAGING</i>
Knock Sensor 1 Circuit Malfunction	P0325	0V - 5V This diagnostic will detect excessive noise on the knock sensor circuit.	<u>SNEF STUCK LOW TEST:</u> Knock is detected for excessive amount of time.	<u>SNEF STUCK LOW TEST:</u> DTC P0327 not active Engine Run Time \geq 120 seconds System voltage > 10V but \leq 17.1V	<u>SNEF STUCK LOW TEST:</u> 10 test failures within a 100 test sample. Test is run every 500 msec. Time necessary to run test: 50 seconds	DTC Type B
Knock Sensor 1 Circuit - Low Input	P0327	0V - 5V This diagnostic will detect a lack of noise on the knock sensor circuit.	<u>KNOCK SENSOR UPDATE TEST</u> Learned Minimum noise Value updated with the filtered value every 50 msec. <u>ACTIVE NOISE CHANNEL TEST:</u> Knock sensor noise \leq 50 A/D counts or > 200 A/D counts. (ESC noise - Minimum Noise Value)	<u>KNOCK SENSOR UPDATE TEST:</u> Timing retard \leq 0° System voltage > 10 V but \leq 17.1 V ECT \geq 60° C Engine Run Time \geq 120 seconds Engine speed > 500 RPM but \leq 900 RPM Knock sensor delta noise < 3 counts <u>ACTIVE NOISE CHANNEL TEST:</u> ECT DTC's not active TP sensor DTC's not active Knock sensor update test complete ECT \geq 60° C Engine speed > 2000 RPM but \leq 3000 RPM Throttle position \geq 5.9%	<u>Delta Min Noise to Low</u> 100 failures per ignition cycle Time necessary to complete sample: 50 sec Continuous <u>ACTIVE NOISE CHANNEL TEST:</u> Noise counter \geq 20 counts. 1 count \cong 100 ms	DTC Type B
Crankshaft Position Sensor Circuit-Range	P0336	3X / 4X Signal This diagnostic will detect a loss of crank sensor signal or long time constant intermittent that would result in a "no start" condition.	Crank Position Sensor Signal missing for a time \geq .5 seconds.	Engine Cranking 4 or more Cam Shaft Position Signals Present	\geq 3 seconds During engine crank.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Crankshaft Position Sensor Circuit- Low Input	P0337	3X / 4X Signal This diagnostic will detect a low duty cycle from the crankshaft position sensor.	Crank sensor duty cycle High Ref/Low Ref < .3125	Engine speed < 4000 RPM Air Flow ≥ 5 g/second	15 Ref pulse failures within a 20 sample limit. Time necessary to complete sample: Varies with engine speed Once every TDC	DTC Type B
Crankshaft Position Sensor Circuit- Intermittent Input	P0339	3X / 4X Signal This diagnostic will detect an intermittent crankshaft position signal.	The calculated instantaneous engine speed $\Delta \geq 1000$ RPM or The calculated instantaneous engine speed = 0 RPM and 4 or more cam cycles have occurred for a period of 1 count (2 to 3 seconds)	Air Flow ≥ 5 g/second	10 test failures within a 400 sample limit. Time necessary to complete sample: 5 sec	DTC Type B
Camshaft Position Sensor Circuit Malfunction	P0340	1X Signal This diagnostic will detect if the Cam Sensor signal is present.	Cam Sensor reference pulse is not seen once every 6 cylinders.	Engine Running	If Cam signal is not detected within 1.75 seconds, test has failed. Once every TDC	DTC Type B
Camshaft Position Sensor Circuit Range/Rationality	P0341	1X Signal This diagnostic will determine if the Cam Sensor is synchronized correctly.	Cam Sensor reference pulse is not detected at the correct interval every 6 cylinders.	Engine Running	40 failed tests within a 100 test sample. Time necessary to complete sample: Varies with engine speed Once every TDC	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Exhaust Gas Recirculation - Insufficient Flow Detected	P0401	This diagnostic will determine if there is a reduction in EGR flow.	With EGR valve open, the peak + MAP Δ is monitored over a time of 2 seconds. This value is compared with a threshold from Engine Speed Vs Baro table and the difference computed. The result is statistically filtered (EWMA) and compared to a decision limit. DTC is set when the filtered result exceeds the decision limit.	<p>Test Enable TP sensor DTC's not active MAP DTC's not active VS sensor DTC's not active IAT sensor DTC's not active ECT sensor DTC's not active IAC DTC's not active Linear EGR Pintle Position DTC not active Misfire DTC's not active ECT > 69.8° C Baro > 70 kPa Vehicle Speed > 27 mph IAC Δ < 8 counts AC clutch status is unchanged Transmission status is unchanged</p> <p>Start Test Throttle Position < 1.2% EGR Position < 1% Engine Speed (<i>Manual Transmission</i>): > 1000 rpm but < 1900 rpm (4.3L LD & 5.7L) > 900 rpm but < 1800 rpm (5.0L) Engine Speed (<i>Automatic Transmission</i>): > 800 rpm but < 1600 rpm (5.0L & 5.7L LD) > 800 rpm but < 1900 rpm (5.7L HD) > 900 rpm but < 1600 rpm (4.3L LD) > 900 rpm but < 1700 rpm (4.3L HD) MAP Δ < 1 A/D count (.39 kPa) Compensated MAP > 20 kPa but < 38 kPa Not in DFCO (<i>Automatic Transmission</i>) No change in DFCO state (<i>Manual Transmission</i>)</p> <p>Run Test Stabilized MAP (valve closed) recorded and EGR valve "ramped" open over a time interval and peak MAP value recorded and MAP Δ computed. EGR valve closed</p>	2 seconds Once per trip after EGR I/M Flag is set Maximum of 9 tests per trip until EGR I/M flag set Maximum of 6 tests per trip if a significant deviation from the current EWMA value is detected	DTC Type A
EGR Valve Open Pintle Position Error	P0404	Position error too high	Deviation between actual and desired position > 10% for 10 seconds	Ignition voltage >5V to enable but < 4V to disable	Continuous	DTC Type B
EGR Sensor Signal Low	P0405	Open / Short in pintle feedback system	Pintle position <6 A/D counts for 10 seconds	Ignition voltage > 5V to enable but < 4V to disable	Continuous	DTC Type B
Secondary Air Injection System Malfunction ⑤	P0410	Active: O2 sensors indicate lean condition present when AIR pump is turned on during closed loop operation.	Active: O2 sensor < approx. 222 mv > 1.0 seconds or fuel integrator delta of 21 counts, or 16% when pump turned on during closed loop operation.	Active: No MAF, MAP, IAT, ECT, TPS, O2, VSS, Sys volt, Fuel Trim, misfire, or CCP DTC. Air flow < 25 g/s., engine load < 34 %, PE, DFCO, COT not active. Engine run time after closed loop to enable = 20 seconds in fuel cells 4,5. A/F = 14.7, fuel integrator >= 124 & <= 132, RPM > 550, ECT > 60 C° < 107. Engine load <34 %, ignition volts > 11.7,. Air flow < 25%g/s, IAT > -10°C in fuel cells 5,6.	Active: Up to 3.5 seconds. Up to three times per trip.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Secondary Air Injection System Malfunction ②a,⑨	P0410	Active: O2 sensors indicate lean condition present when AIR pump is turned on during closed loop operation.	Active: O2 sensor < approx. 222 mv > 1.0 seconds or fuel integrator delta of 25 counts, or 20% when pump turned on during closed loop operation.	Active: No MAF, MAP, IAT, ECT, TPS, O2, VSS, Sys volt, Fuel Trim, misfire, or CCP DTC. Air flow < 25 g/s., engine load < 34 %, PE, DFCO, COT not active. Engine run time after closed loop to enable = 20 seconds in fuel cells 4,5. A/F = 14.7, fuel integrator >= 124 & <= 132, RPM > 550, ECT > 60 C° < 107. ignition volts > 11.7.,.	Active: Up to 4 seconds. Up to three times per trip.	DTC Type B
Catalyst System Low Efficiency (Bank 1) ①	P0420	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	OSC Time Difference ≥ 0.0488 sec OSC Time Difference = OSC Worst Pass Thresh - OSC Compensation Factor * (Post Cat O2 Resp Time - Pre Cat O2 Resp Time) OSC Worst Pass Thresh = 0.975 sec	<u>Trip Enable Criteria</u> No AIR DTC's failing No CAM DTC's failing No ECT DTC's failing No EGR DTC's failing No Fuel Trim DTC's failing No IAC DTC's failing No IAT DTC's failing No MAF DTC's failing No MAP DTC's failing No Oxygen Sensor DTC's failing No PRNDL/Transmission DTC's failing No Purge System DTC's failing No TPS DTC's failing No VSS DTC's failing No Misfire DTC's failing <u>Valid Idle Period Criteria</u> Engine Speed ≥ 900 rpm for minimum of 35 sec since end of last idle period. Min engine runtime for stable BLM ≥ 346 sec <u>Test Enable Conditions</u> Predicted Catalyst Temperature ≥ 475°C Closed loop fuel control Barometric Pressure ≥ 73 kPa -6.75 ≤ IAT ≤ 75°C 75°C ≤ ECT ≤ 117°C 0 < Idle Period ≤ 60 sec Tests Attempted this trip ≤ 18 Tests Attempted this idle period = 1 -105 rpm ≤ (Engine Speed - Desired Speed) ≤ 125 rpm <u>Rapid Step Response Enable Criteria</u> OSC Time Difference Step ≥ 0.159 sec OSC Time Difference ≥ 0.000 sec	1 test attempted per valid idle period Maximum of 6 tests per trip until catalyst I/M flag set. Maximum of 1 test per trip after catalyst I/M flag set. frequency: 12.5 ms continuous	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Catalyst System Low Efficiency (Bank 1) ③	P0420	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	OSC Time Difference ≥ 0.110 sec OSC Time Difference = OSC Worst Pass Thresh - OSC Compensation Factor * (Post Cat O2 Resp Time - Pre Cat O2 Resp Time) OSC Worst Pass Thresh = 1.375 sec	<u>Trip Enable Criteria</u> No AIR DTC's failing No CAM DTC's failing No ECT DTC's failing No EGR DTC's failing No Fuel Trim DTC's failing No IAC DTC's failing No IAT DTC's failing No MAF DTC's failing No MAP DTC's failing No Oxygen Sensor DTC's failing No PRNDL/Transmission DTC's failing No Purge System DTC's failing No TPS DTC's failing No VSS DTC's failing No Misfire DTC's failing <u>Valid Idle Period Criteria</u> Engine Speed ≥ 900 rpm for minimum of 35 sec since end of last idle period. Min engine runtime for stable BLM ≥ 346 sec <u>Test Enable Conditions</u> Predicted Catalyst Temperature $\geq 475^{\circ}\text{C}$ Closed loop fuel control Barometric Pressure ≥ 73 kPa $-6.75 \leq \text{IAT} \leq 75^{\circ}\text{C}$ $75^{\circ}\text{C} \leq \text{ECT} \leq 117^{\circ}\text{C}$ $0 < \text{Idle Period} \leq 60$ sec Tests Attempted this trip ≤ 18 Tests Attempted this idle period =1 $-105 \text{ rpm} \leq (\text{Engine Speed} - \text{Desired Speed}) \leq 125$ rpm <u>Rapid Step Response Enable Criteria</u> OSC Time Difference Step ≥ 0.362 sec OSC Time Difference ≥ 0.000 sec	1 test attempted per valid idle period Maximum of 6 tests per trip until catalyst I/M flag set. Maximum of 1 test per trip after catalyst I/M flag set. frequency: 12.5 ms continuous	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Catalyst System Low Efficiency (Bank 1) ④	P0420	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	OSC Time Difference >= 0.3 (automatic) 0.35 (manual) OSC Time Difference = OSC Worst Pass Thresh. - [OSC Compensation Factor * (Post Cat O2 Resp.Time - Pre Cat O2 Resp.Time)] OSC Worst Pass Thresh. = 1.013 (automatic) 1.263 (manual)	<p><u>Trip Enable Criteria:</u> None of the following DTC's failing: AIR, ECT; Fuel Trim; EST; EGR; CAM; IAC; IAT; MAF; MAP; Oxygen Sensor; Purge System; TPS; VSS; Misfire; PRNDL/Trans.(auto.)</p> <p><u>Valid Idle Period Criteria:</u> Engine speed >= 1000 rpm for minimum of 32 sec. (automatics) or 40 sec. (manuals) since end of last idle period. Min. engine run time for stable BLM &INT >= 360 sec.</p> <p><u>Test Enable Conditions:</u> Predicted Catalyst Temperature >= 390°C Closed loop fuel control Barometric Pressure >= 72 kPa -6.75 <= IAT <= 75°C 75 <= ECT <= 118°C 0 <= Idle period <= 120 seconds Tests Attempted this trip <= 6 Tests Attempted this idle period <= 1 -110 rpm <= (Engine Speed - Desired Speed) <= 125 rpm</p>	1 test attempted per valid idle period Maximum of 6 tests per trip until catalyst I/M flag set Maximum of 1 test per trip after catalyst I/M flag set frequency: 12.5 msec. Continuous	DTC Type A
Catalyst System Low Efficiency (Bank 1) ⑤	P0420	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	OSC Time Difference >= 0.092 OSC Time Difference = OSC Worst Pass Thresh. - [OSC Compensation Factor * (Post Cat O2 Resp.Time - Pre Cat O2 Resp.Time)] OSC Worst Pass Thresh. = 0.925	<p><u>Trip Enable Criteria:</u> None of the following DTC's failing: AIR, ECT; Fuel Trim; EST; EGR; CAM; IAC; IAT; MAF; MAP; Oxygen Sensor; Purge System; TPS; VSS; Misfire; PRNDL/Trans.(auto.)</p> <p><u>Valid Idle Period Criteria:</u> Engine speed >= 800 rpm for minimum of 40 sec. since end of last idle period. Min. engine run time for stable BLM &INT >= 360 sec.</p> <p><u>Test Enable Conditions:</u> Predicted Catalyst Temperature >= 390°C Closed loop fuel control Barometric Pressure >= 72 kPa -6.75 <= IAT <= 75°C 75 <= ECT <= 118°C 0 <= Idle period <= 120 seconds Tests Attempted this trip <= 6 Tests Attempted this idle period <= 1 -110 rpm <= (Engine Speed - Desired Speed) <= 125 rpm</p>	1 test attempted per valid idle period Maximum of 6 tests per trip until catalyst I/M flag set Maximum of 1 test per trip after catalyst I/M flag set frequency: 12.5 msec. Continuous	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Catalyst System Low Efficiency (Bank 1) ⑥	P0420	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	<p>OSC Time Difference >= 0.1125 (automatic) 0.126 (manual)</p> <p>OSC Time Difference = OSC Worst Pass Thresh. - [OSC Compensation Factor * (Post Cat O2 Resp.Time - Pre Cat O2 Resp.Time)]</p> <p>OSC Worst Pass Thresh. = 1.3 (automatic) 1.463 (manual)</p>	<p>Trip Enable Criteria: None of the following DTC's failing: AIR, ECT; Fuel Trim; EST; EGR; CAM; IAC; IAT; MAF; MAP; Oxygen Sensor; Purge System; TPS; VSS; Misfire; PRNDL/Trans.(auto.)</p> <p>Valid Idle Period Criteria: Engine speed >= 1100 rpm for minimum of 43.5 sec. (manuals) or 900 rpm for minimum of 32 sec. (automatics) since end of last idle period. Min. engine run time for stable BLM &INT >= 360 sec.</p> <p>Test Enable Conditions: Predicted Catalyst Temperature >= 390°C Closed loop fuel control Barometric Pressure >= 72 kPa -6.75 <= IAT <= 75°C 75 <= ECT <= 118°C 0 <= Idle period <= 120 seconds Tests Attempted this trip <= 6 Tests Attempted this idle period <= 1 -110 rpm <= (Engine Speed - Desired Speed) <= 125 rpm</p>	<p>1 test attempted per valid idle period</p> <p>Maximum of 6 tests per trip until catalyst I/M flag set</p> <p>Maximum of 1 test per trip after catalyst I/M flag set</p> <p>frequency: 12.5 msec. Continuous</p>	DTC Type A
Catalyst System Low Efficiency (Bank 1) ⑦	P0420	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	<p>OSC Time Difference >= 0.225</p> <p>OSC Time Difference = OSC Worst Pass Thresh. - [OSC Compensation Factor * (Post Cat O2 Resp.Time - Pre Cat O2 Resp.Time)]</p> <p>OSC Worst Pass Thresh. = 2.6</p>	<p>Trip Enable Criteria: None of the following DTC's failing: AIR, ECT; Fuel Trim; EST; EGR; CAM; IAC; IAT; MAF; MAP; Oxygen Sensor; Purge System; TPS; VSS; Misfire; PRNDL/Trans.(auto.)</p> <p>Valid Idle Period Criteria: Engine speed >= 900 rpm for minimum of 42 sec. since end of last idle period. Min. engine run time for stable BLM &INT >= 360 sec.</p> <p>Test Enable Conditions: Predicted Catalyst Temperature >= 385°C Closed loop fuel control Barometric Pressure >= 72 kPa -6.75 <= IAT <= 75°C 75 <= ECT <= 118°C 0 <= Idle period <= 120 seconds Tests Attempted this trip <= 6 Tests Attempted this idle period <= 1 -110 rpm <= (Engine Speed - Desired Speed) <= 125 rpm</p>	<p>1 test attempted per valid idle period</p> <p>Maximum of 6 tests per trip until catalyst I/M flag set</p> <p>Maximum of 1 test per trip after catalyst I/M flag set</p> <p>frequency: 12.5 msec. Continuous</p>	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Catalyst System Low Efficiency (Bank 2) ⑥	P0430	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	OSC Time Difference >= 0.1125 (automatic) 0.303 (manual) OSC Time Difference = OSC Worst Pass Thresh. - [OSC Compensation Factor * (Post Cat O2 Resp.Time - Pre Cat O2 Resp.Time)] OSC Worst Pass Thresh. = 1.313 (automatic) 2.675 (manual)	<p><u>Trip Enable Criteria:</u> None of the following DTC's failing: AIR, ECT; Fuel Trim; EST; EGR; CAM; IAC; IAT; MAF; MAP; Oxygen Sensor; Purge System; TPS; VSS; Misfire; PRNDL/Trans.(auto.)</p> <p><u>Valid Idle Period Criteria:</u> Engine speed >= 1100 rpm for minimum of 43.5 sec. (manuals) or 900 rpm for minimum of 32 sec. (automatics) since end of last idle period. Min. engine run time for stable BLM &INT >= 360 sec.</p> <p><u>Test Enable Conditions:</u> Predicted Catalyst Temperature >= 390°C Closed loop fuel control Barometric Pressure >= 72 kPa -6.75 <= IAT <= 75°C 75 <= ECT <= 118°C 0 <= Idle period <= 120 seconds Tests Attempted this trip <= 6 Tests Attempted this idle period <= 1 -110 rpm <= (Engine Speed - Desired Speed) <= 125 rpm</p>	1 test attempted per valid idle period Maximum of 6 tests per trip until catalyst I/M flag set Maximum of 1 test per trip after catalyst I/M flag set frequency: 12.5 msec. Continuous	DTC Type A
Catalyst System Low Efficiency (Bank 2) ⑦	P0430	This diagnostic will determine the efficiency (oxygen storage capacity) of the catalytic converter.	OSC Time Difference >= 0.237 OSC Time Difference = OSC Worst Pass Thresh. - [OSC Compensation Factor * (Post Cat O2 Resp.Time - Pre Cat O2 Resp.Time)] OSC Worst Pass Thresh. = 2.3	<p><u>Trip Enable Criteria:</u> None of the following DTC's failing: AIR, ECT; Fuel Trim; EST; EGR; CAM; IAC; IAT; MAF; MAP; Oxygen Sensor; Purge System; TPS; VSS; Misfire; PRNDL/Trans.(auto.)</p> <p><u>Valid Idle Period Criteria:</u> Engine speed >= 900 rpm for minimum of 42 sec. since end of last idle period. Min. engine run time for stable BLM &INT >= 360 sec.</p> <p><u>Test Enable Conditions:</u> Predicted Catalyst Temperature >= 385°C Closed loop fuel control Barometric Pressure >= 72 kPa -6.75 <= IAT <= 75°C 75 <= ECT <= 118°C 0 <= Idle period <= 120 seconds Tests Attempted this trip <= 6 Tests Attempted this idle period <= 1 -110 rpm <= (Engine Speed - Desired Speed) <= 125 rpm</p>	1 test attempted per valid idle period Maximum of 6 tests per trip until catalyst I/M flag set Maximum of 1 test per trip after catalyst I/M flag set frequency: 12.5 msec. Continuous	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Evap. Emission Control System Malfunction	P0440	0.1 V - 4.98V This DTC will detect a weak vacuum condition (large leak or restriction) in the Evap. system.	<p><u>WEAK VACUUM TEST- STAGE I (Cold Test):</u> Tank Vac. < 13 or 9 in. H₂O <u>depending on application</u> <u>WEAK VACUUM TEST- STAGE II (Warm Test):</u> Stage I test failed previous trip and this trip. Tank Vac. < 11 in. H₂O</p> <p align="center">OR</p> <p>If HC vapor is not present and the SMALL LEAK TEST has failed.</p>	<p><u>TEST ENABLE :</u> MAP DTC's not active TP Sensor DTC's not active VS Sensor DTC's not active O2 Sensor DTC's not active ECT Sensor DTC's not active DTC P0125 not active IAT Sensor DTC's not active Fuel Level >12.5% but < 87.5% Powerup Vacuum Test Fail = False System Voltage > 10V but < 17V</p> <p><u>COLD START TEST:</u> ECT > 3.75°C but < 30° C IAT > 3.75°C but < 30° C Cold Temperature Δ (ECT - IAT): < 1.5°C if IAT > ECT < 8.25 °C if ECT > IAT Baro > 72.5 kPa Fuel Level Input = True Fuel Level Present Test = True</p>	<p><u>WEAK VACUUM TEST- STAGE I (Cold Test):</u> Fault present for a time ≥ 30 , 50 or 80 depending on application sec. (Vac. Weighted)</p> <p><u>WEAK VACUUM TEST- STAGE II (Warm Test):</u> Fault present for a time ≥ 1400 sec.</p> <p>Once per cold start</p>	DTC Type A (Behaves as a Type B)
Evap. Emission Control System Leak Detected (Small Leak)	P0442	0.1 V - 4.98V This DTC will detect a small leak in the Evap. system between the fuel fill cap and up to but not including the purge solenoid.	<p><u>SMALL LEAK TEST FAIL:</u> Vacuum < 7 , 9 or 11" H₂O for a time < 25,30 or 35 sec. Depending on application Vacuum Decay (determined by fuel level and intake temperature) ≥ a value determined by Start Vacuum minus Tank Vacuum for a period ≥ 15 or 12 seconds. Vacuum > 0.1 in. H₂O for a time ≤ 35 , 50,60,80,85seconds. depending on application</p>	<p><u>TEST ENABLE :</u> MAP DTC's not active TP Sensor DTC's not active VS Sensor DTC's not active O2 Sensor DTC's not active ECT Sensor DTC's not active DTC P0125 not active IAT Sensor DTC's not active Fuel Level >12.5% but < 87.5%</p> <p><u>COLD START TEST:</u> ECT > 3.75°C but < 30° C IAT > 3.75°C but < 30° C Cold Temperature Δ (ECT - IAT): < 1.5°C if IAT > ECT < 8.25 °C if ECT > IAT Baro > 72.5 kPa Fuel Level Input = True Fuel Level Present Test = True</p> <p><u>FUEL SLOSH TEST:</u> Tank Vacuum Δ ≤ 0.6 in. H₂O OR Fuel Level Δ ≤ 7.8%</p> <p><u>WEAK VACUUM TEST (Stage I) :</u> Throttle position < 75% Vehicle speed < 65 mph Tank Vacuum ≥ 9 ,11,13in. H₂O within 30,50,80 depending on app. seconds.</p>	<p>Vacuum Decay ≥ 12 or 15 seconds</p> <p>Once per cold start</p>	DTC Type A (Behaves as a Type B)

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Evap. Emission Control System Vent Control Malfunction	P0446	This DTC will determine if a restriction is present in the vent solenoid, vent filter, vent hose or canister.	<u>EXCESS VACUUM TEST - STAGE I</u> : Vent solenoid commanded OPEN Fuel Tank Vacuum \geq 7 in. H ₂ O for 2 seconds(monitored during initial purge ramp) OR <u>EXCESS VACUUM TEST - STAGE II</u> <u>II</u> : Vent solenoid commanded OPEN during normal purge. Fuel Tank Vacuum \geq 12.9 in. H ₂ O for a time \geq 4 seconds	<u>TEST ENABLE :</u> MAP DTC's not active TP Sensor DTC's not active VS Sensor DTC's not active O2 Sensor DTC's not active ECT Sensor DTC's not active DTC P0125 not active IAT Sensor DTC's not active Fuel Level >12.5% but < 87.5% System Voltage > 10V but < 17V <u>COLD START TEST:</u> ECT > 3.75°C but < 30° C IAT > 3.75°C but < 30° C Cold Temperature Δ (ECT - IAT): < 1.5°C if IAT > ECT < 8.25 °C if ECT > IAT Baro > 72.5 kPa Fuel Level Input = True Fuel Level Present Test = True <u>FUEL SLOSH TEST:</u> Tank Vacuum $\Delta \geq$ 0.6 in. H ₂ O OR Fuel Level $\Delta \geq$ 7.8% <u>PURGE HC PRESENT :</u> Purge Closed Loop Multiplier \geq 0.6 for a time \leq a table value based on coolant temperature <u>WEAK VACUUM TEST -Stage I:</u> Tank Vacuum \geq 9 11 or 13in. H ₂ O within 30,50,80 seconds. depending on application	<u>EXCESS VACUUM TEST - STAGE II:</u> 180 seconds Once per cold start at: • Powerup • Excess Vac. Stage I • Excess Vac. Stage II	DTC Type A
EVAP Fuel Tank Pressure Sensor Circuit Low Voltage	P0452	This DTC will detect a vacuum sensor stuck low	tank vacuum raw voltage < 0.1 volt for 5 seconds	<u>runs countiously after a 1 second delay for sensor warmup</u>		DTC Type B
EVAP Fuel Tank Pressure Sensor Circuit High Voltage	P0453	This DTC will detect a vacuum sensor stuck hi	tank vacuum raw voltage >4.98 volt for 5 seconds	<u>runs countiously after a 1 second delay for sensor warmup</u>		DTC Type B
Vehicle Speed (VS) Sensor Signal Missing	P0500	The DTC detects a missing vehicle speed sensor signal, generally on an overrun or decel condition.	Vehicle Speed \leq 1 MPH	MAP sensor DTC's not active MAP < 20 kPa Coolant Temperature \geq 60° C Engine > 1400 RPM but < 4400 RPM Throttle Position < 3.125 %	Failing > 5 seconds Continuous	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Idle Control System RPM Lower Than Expected	P0506	This DTC will determine if a low idle is the result of a IAC valve or circuit. A low idle is defined as 75 RPM below the desired idle.	Air flow $\Delta < 3$ g/s	<p><u>Test Enable: (non - intrusive)</u> TP sensor DTC's not active VS sensor DTC's not active ECT DTC's not active MAP DTC's not active ECT > 50°C System Voltage > 10V but < 16 V IAT > -25°C Engine run time > 30 seconds Baro > 70 kPa TP < 1% VS < 2 MPH Above met for a time > 3 seconds to enable diagnostic. If non-intrusive test fails, intrusive test is run.</p> <p><u>Run Test: (intrusive)</u> Air Flow > 17.5 g/sec but < 50 g/sec VS > 25 MPH but < 85 MPH TP $\Delta < 1\%$ Engine Speed $\Delta < 50$ RPM IAC motor commanded 10 %/ 100 msec.</p>	10 seconds Continuous after enable	DTC Type B
Idle Control System RPM Higher Than Expected	P0507	This DTC will determine if a high idle is the result of a IAC valve or circuit. A high idle is defined as 100 RPM above the desired idle.	Air flow $\Delta < 3$ g/s	<p><u>Test Enable: (non - intrusive)</u> TP sensor DTC's not active VS sensor DTC's not active ECT DTC's not active MAP DTC's not active ECT > 50°C System Voltage > 10V but < 16 V IAT > -25°C Engine run time > 30 seconds Baro > 70 kPa TP < 1% VS < 2 MPH Above met for a time > 3 seconds to enable diagnostic. If non-intrusive test fails, intrusive test is run.</p> <p><u>Run Test: (intrusive)</u> Air Flow > 17.5 g/sec but < 50 g/sec VS > 25 MPH but < 85 MPH TP $\Delta < 1\%$ Engine Speed $\Delta < 50$ RPM IAC motor commanded 10 %/ 100 msec.</p>	10 seconds Continuous after enable	DTC Type B
VCM Memory Error - Type 4 (Program Flash)	P0601	This diagnostic checksums the contents of flash EEPROM and compares it to the expected value.	The calculated checksum does not match the programmed value.	-----	Once per trip at controller initialization.	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
VCM Memory Error - Not Programmed	P0602	This diagnostic checks the state of the Service Calibration Bit to determine if the controller needs to be programmed.	The Calibrated No Start For Service bit is true in the calibration.	-----	Once per trip at controller initialization.	DTC Type A
VCM Memory Error - Type 2 (Keep Alive)	P0603	This diagnostic checks that data stored to the Non-Volatile Keep Alive section of memory is functioning correctly.	The checksum of the data does stored at powerdown does not match the checksum of the data present at powerup, and the data read from memory does not match the data that was stored to check memory function.	-----	Once per trip at controller initialization.	DTC Type A
VCM Memory Error - Type 1 (Volatile RAM)	P0604	This diagnostic checks that data stored to the Volatile section of memory is stored correctly.	The data read from the memory location does not match the data that was just stored to that location.	-----	Once per trip at controller initialization.	DTC Type A
VCM Memory Error - Type 3 (Boot Flash)	P0605	This diagnostic checks that the checksum of the Boot Flash section of memory matches a predetermined value.	The checksum of the data does not match the expected checksum.	-----	Once per trip at controller initialization.	DTC Type A
Transmission Clutch Switch Input Malfunction (Manual Trans. Only)	P0704	This DTC monitors the Transmission Clutch Switch for a transition during accelerations to the calibrated speed and back to 0 MPH.	No clutch switch circuit transitions detected	VS sensor DTC's not active Vehicle Speed is now = 0 mph and Vehicle Speed has been > 40 mph The brake switch is not currently pressed. (The clutch switch is wired in series with the brake switch)	2 consecutive test failures Continuous. 100 mS	DTC Type B
①③④⑥⑦⑧						

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2 Sys. Fault - Too Few O2S R/L or L/R Switches, Insufficient Activity (Bank 1, Sensor 1)	P1133	.1V to 1.0V This DTC determines if the O2 sensor functioning properly by monitoring the number of L/R and R/L switches.	Number of switches in 100 seconds: L/R switches < 20 R/L switches < 20	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 Response tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Response Test Enable:</u> Closed loop low MAP not active DTC's P0131, P0132, P0134 and P0135 not active Closed loop ECT > 57°C Engine run time > 75 seconds Air flow ≥ 15 g/s but ≤ 55 g/s Engine speed ≥ 1100 rpm but ≤ 3000 rpm Canister Purge Duty Cycle ≥ 0% Above present for > 2 seconds	100 seconds after closed loop enable Once per key cycle	DTC Type B
O2S Circuit - Transition Time Ratio Malfunction (Bank 1, Sensor 1)	P1134	.1V to 1.0V This DTC determines if the O2 sensor functioning properly by checking the ratio of average response time.	Ratio of average response times: Ratio > 5.0 or < 0.375 *O2 voltage < 300 mV = lean *O2 voltage > 600 mV = rich	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 Response tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage ≥ 11.7 but <18 Volts <u>Response Test Enable:</u> Closed loop low MAP not active DTC's P0131, P0132, P0134 and P0135 not active Closed loop ECT > 57°C Engine run time > 75 seconds Air flow ≥ 15 g/s but ≤ 55 g/s Engine speed ≥ 1100 rpm but ≤ 3000 rpm Canister Purge Duty Cycle ≥ 0% Above present for > 2 seconds	100 seconds after closed loop enable Once per ignition cycle	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2 Sys. Fault - Too Few O2S R/L or L/R Switches, Insufficient Activity (Bank 2, Sensor 1)	P1153	.1V to 1.0V This DTC determines if the O2 sensor functioning properly by monitoring the number of L/R and R/L switches.	Number of switches in 100 seconds: L/R switches < 20 R/L switches < 20	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 Response tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage \geq 11.7 but <18 Volts <u>Response Test Enable:</u> Closed loop low MAP not active DTC's P0151, P0152, P0154 and P0155 not active Closed loop ECT > 57°C Engine run time > 75 seconds Air flow \geq 15 g/s but \leq 55 g/s Engine speed \geq 1100 rpm but \leq 3000 rpm Canister Purge Duty Cycle \geq 0% Above present for > 2 seconds	100 seconds after closed loop enable Once per key cycle	DTC Type B
O2S Circuit - Transition Time Ratio Malfunction (Bank 2, Sensor 1)	P1154	.1V to 1.0V This DTC determines if the O2 sensor functioning properly by checking the ratio of the average response time.	Ratio of average response times: Ratio > 5.0 or < .375 *O2 voltage < 300 mV = lean *O2 voltage > 600 mV = rich	<u>O2 Diagnostic Enable:</u> (the following criteria must be met to enable the O2 Response tests) TP sensor DTC's not active Evap. DTC's not active IAT sensor DTC's not active MAP DTC's not active ECT sensor DTC's not active MAF sensor DTC's not active Misfire DTC's not active No intrusive tests in progress No device controls active System Voltage \geq 11.7 but <18 Volts <u>Response Test Enable:</u> Closed loop low MAP not active DTC's P0151, P0152, P0154 and P0155 not active Closed loop ECT > 57°C Engine run time > 75 seconds Air flow \geq 15 g/s but \leq 55 g/s Engine speed \geq 1100 rpm but \leq 3000 rpm Canister Purge Duty Cycle \geq 0% Above present for > 2 seconds	100 seconds after closed loop enable Once per ignition cycle	DTC Type B
Crankshaft Position System Variation Not Learned (CASE)	P1336	This diagnostic will determine if the Crankshaft Position System Variation has been learned	Engine running	Manufactures Enable counter must be zero	Continuous	DTC Type A

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Camshaft Sensor Misinstalled	P1345	1X Signal This diagnostic will determine if the Cam sensor and high voltage switch have been installed correctly.	Cam signal falling edge out of phase ± 26 degrees from crank falling edge.	-----	30 test failures within a 50 test sample size. Time necessary to complete sample: Varies with engine speed Every crank fall	DTC Type A
EST Output High	P1351	0 V-1V This diagnostic will determine if a failure has occurred due to an open circuit.	EST voltage >4.9 V	EST Enabled Engine speed < 250 RPM	20 test failures Time necessary to complete sample: Executed during crank, approximately 3 seconds. Once per ignition cycle	DTC Type A
EST Not Toggling After Enable	P1361	0 V-1V This diagnostic will determine if a failure has occurred due to a grounded circuit.	EST voltage <.04V	EST Enabled Engine speed < 250 RPM	20 test failures Time necessary to complete sample: Executed during crank, approximately 3 seconds. Once per ignition cycle	DTC Type A
EGR Valve Circuit Performance - actual position greater than commanded	P1404	Detects a valve that is stuck open when commanded closed.	Pintle position > 10 A/D counts from learned closed position for 10 seconds for 3 subroutines	EGR valve strokes to 100% duty cycle between subroutines. Enable parameters for stroke: 80°C < ETC < 120°C IAT < 100°C Desired EGR > 15%	Continuous	DTC Type A
Secondary Air Injection System Malfunction (Bank 1) ②a ⑤ ⑨	P1415	Detects left bank AIR malfunction	Determines if left bank AIR diagnostic failed	Same as P0410. See P0410	See P0410 diagnostic description.	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Secondary Air Injection System Malfunction (Bank 2) ②a ⑤ ⑨	P1416	Dectects right bank AIR malfunction	Determines if right bank AIR diagnostic failed.	Same as P0410. See P0410	See P0410 diagnostic description	DTC Type B
Evap. Emission Control System - Continuous Open Purge Flow	P1441	This DTC will determine if the purge solenoid is leaking.	<u>PURGE VALVE LEAK TEST:</u> Purge Valve closed TP > 0% but < 99.6% Vacuum ≥ 10 KPa Tank Vacuum ≥ 12 in. H ₂ O for 2 sec within ≤ 37.5 seconds after 30 second delay.	<u>TEST ENABLE:</u> MAP DTC's not active TP Sensor DTC's not active VS Sensor DTC's not active O2 Sensor DTC's not active ECT Sensor DTC's not active DTC P0125 not active IAT Sensor DTC's not active Fuel Level >12.5% but < 87.5% System Voltage > 10V but < 17V <u>COLD START TEST:</u> ECT > 3.75°C but < 30° C IAT > 3.75°C but < 30° C Cold Temperature Δ (ECT - IAT): < 1.5°C if IAT > ECT < 8.25 °C if ECT > IAT Baro >72.5 kPa Fuel Level Input = True Fuel Level Present Test = True <u>EXCESS VACUUM TEST -STAGE I:</u> Vent solenoid commanded OPEN Fuel Tank Vacuum < 7 in. H ₂ O <u>WEAK VACUUM TEST -Stage I:</u> Throttle position < 75% Vehicle speed < 65 mph Tank Vacuum ≥ 9, 11 or 13 in. H ₂ O within 30 ,50 or 80seconds.	<u>PURGE VALVE LEAK TEST:</u> 180seconds Max. Once per cold start	DTC Type B

**1999 4.3L (LF6 and L45) C/K-truck, S/T-truck, M/L-van, G-van (GVW < 8500) (includes Isuzu Hombre)
ENGINE DIAGNOSTIC PARAMETERS**

99t43WXLD_yE.doc)

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Idle Air Control - Low	P1508	This DTC will determine if a low idle is the result of an engine mechanical problem. A low idle is defined as 75 RPM below the desired idle.	Air flow $\Delta > 3$ g/s	<p><u>Test Enable: (non - intrusive)</u> TP sensor DTC's not active VS sensor DTC's not active ECT DTC's not active MAP DTC's not active ECT > 50°C System Voltage > 10V but < 16 V IAT > -25°C Engine run time > 30 seconds Baro > 70 kPa TP < 1% VS < 2 MPH Above met for a time > 3 seconds to enable diagnostic. If non-intrusive test fails, intrusive test is run.</p> <p><u>Run Test: (intrusive)</u> Air Flow > 17.5 g/sec but < 50 g/sec VS > 25 MPH but < 85 MPH TP $\Delta < 1\%$ Engine Speed $\Delta < 50$ RPM IAC motor commanded 10 %/ 100 msec.</p>	10 seconds Continuous after enable	DTC Type B
Idle Air Control - High	P1509	This DTC will determine if a high idle is the result of an engine mechanical problem. A high idle is defined as 100 RPM above the desired idle.	Air flow $\Delta > 3$ g/s	<p><u>Test Enable: (non - intrusive)</u> TP sensor DTC's not active VS sensor DTC's not active ECT DTC's not active MAP DTC's not active ECT > 50°C System Voltage > 10V but < 16 V IAT > -25°C Engine run time > 30 seconds Baro > 70 kPa TP < 1% VS < 2 MPH Above met for a time > 3 seconds to enable diagnostic. If non-intrusive test fails, intrusive test is run.</p> <p><u>Run Test: (intrusive)</u> Air Flow > 17.5 g/sec but < 50 g/sec VS > 25 MPH but < 85 MPH TP $\Delta < 1\%$ Engine Speed $\Delta < 50$ RPM IAC motor commanded 10 %/ 100 msec.</p>	10 seconds Continuous after enable	DTC Type B