

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
Transmission Control Module (TCM)	C1251	The lateral acceleration signal is stuck at a high magnitude in range	Lateral acceleration magnitude	<= 3.8499999 g's				Special No MIL
			Lateral acceleration magnitude	>= 0.53 g's				
			Lateral acceleration magnitude is within the range above for	>= 75 Sec				
					Lateral acceleration magnitude	<= 3.85 g's		
					Lateral acceleration magnitude	>= 0.53 g's		
					Lateral acceleration magnitude is within the range above for	>= 60 Sec		
					Diagnostic shifting override command	= Faux Boolean		
					Attained Gear State	= 1st through 6th		
					Attained Gear Slip	<= 100 RPM		
					Transmission Type	= Clutch to Transmission		
					High Side Driver 1 On	= Vrai Boolean		
					Vehicle Speed	>= 15 kph		
					Battery Voltage	<= 31.99902 Volts		
					Battery Voltage	>= 9 Volts		
					Battery voltage is within the allowable limits for	>= 0.1 Sec		
					Ignition Voltage	<= 31.99902 Volts		
					Ignition Voltage	>= 9 Volts		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Service Fast Learn (SFL) Mode Ignition voltage and SFL conditions met for	= Faux Boolean >= 0.1 Sec		
					<b>Disable Condition s:</b> <b>MIL not Illuminated for DTC's:</b>	TCM: If calibrated to illuminate the MIL (P0716, P0717, P0721, P0722, P0723, P07BF, P07C0, P077B, P077C, P077D, P215C, U0073) ECM: None		
Transmission Control Module (TCM)	P0601	Transmission Electro-Hydraulic Control Module Read Only Memory	Incorrect program/calibrations checksum	= Vrai Boolean	<b>Disable Condition s:</b> <b>MIL not Illuminated for DTC's:</b>	TCM: P0601 ECM: None	>= 5 Fail Counts	One Trip
Transmission Control Module (TCM)	P0603	Transmission Electro-Hydraulic Control Module Long-Term Memory Reset	Non-volatile memory (static or dynamic) checksum failure at Powerup	= Vrai Boolean			Runs Continously	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disable Condition s: MIL not Illuminated for DTC's:	TCM: P0603 ECM: None		
Transmission Control Module (TCM)	P0604	Transmission Electro-Hydraulic Control Module Random Access Memory	RAM Read/Write Failure (Single Word)	= Vrai Boolean	Disable Condition s: MIL not Illuminated for DTC's:	TCM: P0604 ECM: None	>= 5 Fail Counts  = 16 Sample Counts	One Trip
Transmission Control Module (TCM)	P062F	Transmission Electro-Hydraulic Control Module Long Term Memory Performance	TCM Non-Volatile Memory bit Incorrect flag at Powerdown	= Vrai Boolean	Disable Condition s: MIL not Illuminated for DTC's:	TCM: P062F ECM: None	Runs Continously	One Trip
Transmission Control Module (TCM)	P0634	Transmission Electro-Hydraulic Control Module Internal Temperature Too High	<u>Fail Case 1</u>  Substrate Temperature	>= 144 °C			>= 5 Fail Time (Sec)	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<u>Fail Case 2</u> Substrate Temperature Ignition Voltage Note: either fail case can set the DTC	>= 50 °C >= 18 Volts			>= 2 Fail Time (Sec)	
					Ignition Voltage Lo Ignition Voltage Hi Substrate Temp Lo Substrate Temp Hi Substrate Temp Between Temp Range for Time P0634 Status is	>= 9 Volts <= 31.99023 Volts >= 0 °C <= 240 °C >= 0.25 Sec ≠ Test Failed This Key On or Fault Active		
					Disable Condition s: MIL not Illuminated for DTC's:	TCM: None ECM: None		
High Side Driver 1	P0658	Actuator Supply Voltage Circuit Low	The HWIO reports a low voltage (open or ground short) error flag	= Vrai Boolean			>= 4 out of 6 Fail Counts Sample Counts	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					P0658 Status is not  High Side Driver 1 On	= Test Failed = This Key On or Fault Active = True Boolean		
					<b>Disa ble Con diti on s:</b>  <b>MIL not Illuminated for DTC's:</b>	TCM: None ECM: None		
Transmission Control Module (TCM)	P0667	TCM Internal Temp (substrate) Sensor Circuit Range/Performanc -	If transmission oil temp to substrate temp Δ	> Refer to Table 19 in supporting documents °C				Two Trips
			If TCM substrate temp to power up temp Δ	> Refer to Table 20 in supporting documents °C				
			Both conditions above required to increment fail counter  Note: table reference temp = to the median temp of trans oil temp, substrate temp and power up temp.				>= 3000 Fail Counts (100ms loop)  Out of 3750 Sample Counts (100ms loop)	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Non-continuous (intermittent) fail conditions will delay resetting fail counter until				>= 700 Pass Counts (100ms loop)  Out of 875 Sample Counts (100ms loop)	
					Engine Torque Signal Valid = Vrai Boolean Accelerator Position Signal Valid = Vrai Boolean Ignition Voltage Lo >= 9 Volts Ignition Voltage Hi <= 31.99023 Volts Engine Speed Lo >= 400 RPM Engine Speed Hi <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec Brake torque active = Faux			
					Below describes the brake torque entry criteria Engine Torque >= 90 N*m Throttle >= 30.00031 Pct Transmission Input Speed <= 200 RPM Vehicle Speed <= 8 Kph Transmission Range ≠ Park Transmission Range ≠ Neutral PTO = Not Active			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Set Brake Torque Active TRUE if above conditions are met for:	>= 7 sec		
					Below describes the brake torque exit criteria			
					Brake torque entry criteria	= Not Met		
					Clutch hydraulic pressure	≠ Clutch Hydraulic Air Purge Event		
					Clutch used to exit brake torque active	= CeTFTD_ e_C3_Rat IEnbl		
					The above clutch pressure is greater than this value for one loop	>= 600 kpa		
					Set Brake Torque Active FALSE if above conditions are met for:	>= 20 Sec		
					P0667 Status is	≠ Test Failed This Key On or Fault Active		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: P0658, P0668, P0669, P06AD, P06AE, P0716, P0712, P0713, P0717, P0722, P0723, P0962, P0963, P0966, P0967, P0970, P0971, P215C, P2720, P2721, P2729, P2730  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Transmission Control Module (TCM)	P0668	TCM internal temperature (substrate) thermistor failed at a low volatge	Type of Sensor Used  If TCM Substrate Temperature Sensor = Direct Proportional and Temp  If TCM Substrate Temperature Sensor = Indirect Proportional and Temp	CeTFTL_e_ VoltageInv erseProp  <= 254 °C  >= 254 °C				Two Trips
			Either condition above will satisfy the fail conditions				>= 60 Fail Timer (Sec)	



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Ignition Voltage Lo Ignition Voltage Hi Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for  P0668 Status is	>= 9 Volts <= 31.99023 Volts >= 400 RPM <= 7500 RPM >= 5 Sec  Test Failed This Key On or Fault Active  TCM: None ECM: None		
					<b>Disa ble Con diti on s:</b>	<b>MIL not Illuminated for DTC's:</b>		
Transmission Control Module (TCM)	P0669	TCM internal temperature (substrate) thermistor failed at a high voltage	Type of Sensor Used	CeTFTI_e_ VoltageInv erseProp				Two Trips
			If TCM Substrate Temperature Sensor = Direct Proportional and Temp	>= -254 °C				
			If TCM Substrate Temperature Sensor = Indirect Proportional and Temp	<= -254 °C				
			Either condition above will satisfy the fail conditions				>= 60	Fail Timer (Sec)

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					P0669 Status is	≠ Test Failed This Key On or Fault Active		
					For Hybrids, below conditions must also be met			
					Estimated Motor Power Loss	>= 0 kW		
					Estimated Motor Power Loss greater than limit for time	>= 0 Sec		
					Lost Communication with Hybrid Processor Control Module	= Faux		
					Estimated Motor Power Loss Fault	= Faux		
				Disable Conditions:	MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723 ECM: None		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.	
Transmission Control Module (TCM)	P06AC	TCM Power-up Temp Sensor Circuit Range/Performanc	If TCM power-up temp to substrate temp Δ	>	Refer to Table 20 in supporting documents °C			Two Trips	
			If transmission oil temp to power up temp Δ	>	Refer to Table 18 in supporting documents °C				
			Both conditions above required to increment fail counter						>= 3000 Fail Counts (100ms loop)
			Note: table reference temp = to the median temp of trans oil temp, substrate temp and power up temp.						Out of 3750 Sample Counts (100ms loop)
			Non-continuous (intermittent) fail conditions will delay resetting fail counter until						>= 700 Pass Counts (100ms loop)
					Engine Torque Signal Valid	=	Vrai	Boolean	
					Accelerator Position Signal Valid	=	Vrai	Boolean	
					Ignition Voltage Lo	>=	9	Volts	
					Ignition Voltage Hi	<=	31.99023	Volts	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Brake torque active	= Faux		
					Below describes the brake torque entry criteria			
					Engine Torque	>= 90 N*m		
					Throttle	>= 30.00031 Pct		
					Transmission Input Speed	<= 200 RPM		
					Vehicle Speed	<= 8 Kph		
					Transmission Range	≠ Park		
					Transmission Range	≠ Neutral		
					PTO	= Not Active		
					Set Brake Torque Active TRUE if above conditions are met for:	>= 7 sec		
					Below describes the brake torque exit criteria			
					Brake torque entry criteria	= Not Met		
					Clutch hydraulic pressure	≠ Clutch Hydraulic Air Purge Event		
					Clutch used to exit brake torque active	= CeTFTD_e_C3_Rat IEnbl		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					<p>The above clutch pressure is greater than this value for one loop</p> <p>Set Brake Torque Active FALSE if above conditions are met for:</p> <p>P06AC Status is</p>	<p>&gt;= 600 kpa</p> <p>&gt;= 20 Sec</p> <p>≠ Test Failed This Key On or Fault Active</p>		
					<p><b>Disa ble Con diti on s:</b></p> <p><b>MIL not Illuminated for DTC's:</b></p>	<p>TCM: P0658, P0668, P0669, P06AD, P06AE, P0716, P0712, P0713, P0717, P0722, P0723, P0962, P0963, P0966, P0967, P0970, P0971, P215C, P2720, P2721, P2729, P2730</p> <p>ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E</p>		
Transmission Control Module (TCM)	P06AD	TCM power-up thermistor circuit voltage low	Power Up Temp	<= 254 °C			>= 60 Fail Time (Sec)	Two Trips
					Ignition Voltage Lo	>= 9 Volts		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Ignition Voltage Hi Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for  P06AD Status is  For Hybrids, below conditions must also be met Estimated Motor Power Loss Estimated Motor Power Loss greater than limit for time Lost Communication with Hybrid Processor Control Module Estimated Motor Power Loss Fault	<= 31.99023 Volts >= 400 RPM <= 7500 RPM >= 5 Sec  ≠ Test Failed This Key On or Fault Active  = Faux  = Faux		
					Disa ble Cond ition s:	MIL not illuminated for DTC's: TCM: P0716, P0717, P0722, P0723 ECM: None		
Transmission Control Module (TCM)	P06AE	TCM power-up thermistor circuit voltage high	Power Up Temp	>= -254 °C			>= 60 Fail Time (Sec)	Two Trips

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Ignition Voltage Lo Ignition Voltage Hi Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for  P06AE Status is	>= 9 Volts <= 31.99023 Volts >= 400 RPM <= 7500 RPM >= 5 Sec  Test Failed This Key On or Fault Active		
					<b>Disa ble Con diti on s:</b>	<b>MIL not Illuminated for DTC's:</b>	TCM: None ECM: None	
Transmission Fluid Temperature Sensor (TFT)	P0711	Trans Fluid Temp Sensor Circuit Range/Performanc e	If transmission oil temp to substrate temp Δ	>	Refer to Table 19 in supporting documents °C			Two Trips
			If transmission oil temp to power up temp Δ	>	Refer to Table 18 in supporting documents °C			
			Both conditions above required to increment fail counter				>= 3000	Fail Counts (100ms loop)

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Note: table reference temp = to the median temp of trans oil temp, substrate temp and power up temp.				Out of 3750 Sample Counts (100ms loop)	
			Non-continuous (intermittent) fail conditions will delay resetting fail counter until				>= 700 Pass Counts (100ms loop)	
							Out of 875 Sample Counts (100ms loop)	
					Engine Torque Signal Valid	= Vrai Boolean		
					Accelerator Position Signal Valid	= Vrai Boolean		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Brake torque active	= Faux		
					Below describes the brake torque entry criteria			
					Engine Torque	>= 90 N*m		
					Throttle	>= 30.00031 Pct		
					Transmission Input Speed	<= 200 RPM		
					Vehicle Speed	<= 8 Kph		



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Transmission Range	≠ Park		
					Transmission Range	≠ Neutral		
					PTO	= Not Active		
					Set Brake Torque Active TRUE if above conditions are met for:	>= 7 sec		
					Below describes the brake torque exit criteria			
					Brake torque entry criteria	= Not Met		
					Clutch hydraulic pressure	≠ Clutch Hydraulic Air Purge Event		
					Clutch used to exit brake torque active	= CeTFTD_ e_C3_Rat lEnbl		
					The above clutch pressure is greater than this value for one loop	>= 600 kpa		
					Set Brake Torque Active FALSE if above conditions are met for:	>= 20 Sec		
					P0711 Status is	≠ Test Failed This Key On or Fault Active		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: P0658, P0668, P0669, P06AD, P06AE, P0716, P0712, P0713, P0717, P0722, P0723, P0962, P0963, P0966, P0967, P0970, P0971, P215C, P2720, P2721, P2729, P2730  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Transmission Fluid Temperature Sensor (TFT)	P0712	Transmission fluid temperature thermistor failed at a low voltage	Type of Sensor Used  If Transmission Fluid Temperature Sensor = Direct Proportional and Temp  If Transmission Fluid Temperature Sensor = Indirect Proportional and Temp	=  CeTFTI_e_ VoltageInv erseProp  <= 254 °C  >= 254 °C				Two Trips
			Either condition above will satisfy the fail conditions				>= 60 Fail Time (Sec)	
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for  P0712 Status is  For Hybrids, below conditions must also be met Estimated Motor Power Loss Estimated Motor Power Loss greater than limit for time Lost Communication with Hybrid Processor Control Module Estimated Motor Power Loss Fault	>= 400 RPM <= 7500 RPM >= 5 Sec  ≠ Test Failed This Key On or Fault Active  >= 0 kW >= 0 Sec = Faux = Faux		
					Disa ble Con dition s:	MIL not Illuminated for DTC's: TCM: P0716, P0717, P0722, P0723 ECM: None		
Transmission Fluid Temperature Sensor (TFT)	P0713	Transmission fluid temperature thermistor failed at a high voltage	Type of Sensor Used	CeTFTI_e_ VoltageInv erseProp				Two Trips

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.	
			If Transmission Fluid Temperature Sensor = Direct Proportional and Temp >= -254 °C  If Transmission Fluid Temperature Sensor = Indirect Proportional and Temp <= -254 °C						
			Either condition above will satisfy the fail conditions				>= 60	Fail Time (Sec)	
					Ignition Voltage Lo >= 9 Volts Ignition Voltage Hi <= 31.99023 Volts Engine Speed Lo >= 400 RPM Engine Speed Hi <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec  P0713 Status is ≠ Test Failed This Key On or Fault Active				
					Disa ble Con diti on s:  MIL not Illuminated for DTC's:  TCM: P0713, P0716, P0717, P0722, P0723  ECM: None				
Transmission Input Speed Sensor (TISS)	P0716	Input Speed Sensor Performance	Transmission Input Speed Sensor Drops	>= 1350 RPM			>= 0.8	Fail Time (Sec)	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Torque is	>= 0 N*m		
					Engine Torque is	<= 8191.875 N*m		
					Engine Speed	>= 400 RPM		
					Engine Speed	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Vehicle Speed is	>= 10 Kph		
					Throttle Position is	>= 0 Pct		
					-----			
					Transmission Input Speed is	>= 0 RPM		
					The previous requirement has been satisfied for	>= 0 Sec		
					-----			
					The change (loop to loop) in transmission input speed is	< 8191.75 RPM/Loop		
					The previous requirement has been satisfied for	>= 0 Sec		
					Throttle Position Signal Valid	= Vrai Boolean		
					Engine Torque Signal Valid	= Vrai Boolean		
					Ignition Voltage	>= 9 Volts		
					Ignition Voltage	<= 31.99023 Volts		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					P0716 Status is not	Test Failed = This Key On or Fault Active		
					<b>Disa ble Con diti on s:</b>	<b>MIL not Illuminated for DTC's:</b> TCM: P0717, P0752, P0973, P0974 ECM: P0101, P0102, P0103, P0121, P0122, P0123		
Transmission Input Speed Sensor (TISS)	P0717	Input Speed Sensor Circuit Low Voltage	<u>Fail Case 1</u> Transmission Input Speed is	< 33 RPM			>= 4.5 Fail Time (Sec)	One Trip
			<u>Fail Case 2</u> When P0722 DTC Status equal to Test Failed and Transmission Input Speed is	< 1000 RPM	Controller uses a single power supply for the speed sensors	= 1 Boolean		
					Engine Torque is	>= 50 N*m		
					Engine Torque is	<= 8191.875 N*m		
					Vehicle Speed	>= 16 Kph		
					Engine Torque Signal Valid	= Vrai Boolean		
					Ignition Voltage	>= 9 Volts		
					Ignition Voltage	<= 31.99023 Volts		
					Engine Speed	>= 400 RPM		
					Engine Speed	<= 7500 RPM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.	
					Engine Speed is within the allowable limits for  P0717 Status is not  <b>Disable Condition s:</b> <b>MIL not Illuminated for DTC's:</b>	>= 5 Sec  Test Failed This Key On or Fault Active  TCM: P0722, P0723 ECM: P0101, P0102, P0103			
Transmission Output Speed Sensor (TOSS)	P0722	Output Speed Sensor Circuit Low Voltage	Transmission Output Speed Sensor Raw Speed	<= 35 RPM			>= 4.5	Fail Time (Sec)	One Trip
						P0722 Status is not  Transmission Input Speed Check Engine Torque Check Throttle Position Transmission Fluid Temperature Disable this DTC if the PTO is active Engine Torque Signal Valid	= This Key On or Fault Active = Vrai Boolean = Vrai Boolean >= 8.000183 Pct >= -40 °C = 1 Boolean = Vrai Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Throttle Position Signal Valid	= Vrai Boolean		
					Ignition Voltage is	>= 9 Volts		
					Ignition Voltage is	<= 31.99023 Volts		
					Engine Speed is	>= 400 RPM		
					Engine Speed is	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Enable_Flags Defined Below			
					The Engine Torque Check is TRUE, if either of the two following conditions are TRUE			
					Engine Torque Condition 1			
					Range Shift Status	≠ Range shift completed ENUM		
					OR			
					Transmission Range is	= Park or Neutral		
					Engine Torque is	>= 8191.75 N*m		
					Engine Torque is	<= 8191.75 N*m		
					Engine Torque Condition 2			
					Engine Torque is	>= 30 N*m		
					Engine Torque is	<= 8191.75 N*m		



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					----- The Transmission Input Speed (TIS) Check is TRUE, if either of the two following conditions are TRUE			
					TIS Check Condition 1 Transmission Input Speed is	>= 1000 RPM		
					Transmission Input Speed is	<= 8191.75 RPM		
					TIS Check Condition 2 Engine Speed without the brake applied is	>= 3200 RPM		
					Engine Speed with the brake applied is	>= 3200 RPM		
					Engine Speed is	<= 8191.75 RPM		
					Controller uses a single power supply for the speed sensors	= 1 Boolean		
					Powertrain Brake Pedal is Valid	= Vrai Boolean		
				Disa ble Con diti on s:	MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0723  ECM: P0101, P0102, P0103, P0121, P0122, P0123		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.	
Transmission Output Speed Sensor (TOSS)	P0723	Output Speed Sensor Circuit Intermittent	Transmission Output Speed Sensor Raw Speed	>= 105 RPM			>= 0	Enable Time (Sec)	One Trip
			Output Speed Delta	<= 8191.75 RPM			>= 0	Enable Time (Sec)	
			Output Speed Drop	> 1000 RPM			>= 3	Output Speed Drop Recover y Fail Time (Sec)	
			AND Transmission Range is	= Driven range (R,D)					
					----- Range_Disable OR ----- Neutral_Range_Enable And Neutral_Speed_Enable are TRUE concurrently -----	= Faux See Below			
					Transmission_Range_Enabled Transmission_Input_Speed_Enable No Change in Transfer Case Range (High <-> Low) for	= Vrai See Below = Vrai See Below >= 5 Seconds			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					P0723 Status is not	= Test Failed This Key On or Fault Active		
					Disable this DTC if the PTO is active	= 1 Boolean		
					Ignition Voltage is	>= 9 Volts		
					Ignition Voltage is	<= 31.99023 Volts		
					Engine Speed is	>= 400 RPM		
					Engine Speed is	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Enable_Flags Defined Below			
					Transmission_Input_Speed_Enable is TRUE when either TIS Condition 1 or TIS Condition 2 is TRUE:			
					TIS Condition 1 is TRUE when both of the following conditions are satisfied for	>= 0 Enable Time (Sec)		
					Input Speed Delta	<= 4095 RPM		
					Raw Input Speed	>= 500 RPM		
					TIS Condition 2 is TRUE when ALL of the next two conditions are satisfied			
					Input Speed	= 0 RPM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					A Single Power Supply is used for all speed sensors -----	= Vrai Boolean		
					Neutral_Range_Enable is TRUE when any of the next 3 conditions are TRUE  Transmission Range is  Transmission Range is  Transmission Range is  And when a drop occurs  Loop to Loop Drop of Transmission Output Speed is -----	= Neutral ENUM  = Reverse/ Neutral Transiton al ENUM  = Neutral/Dr ive Transiton al ENUM  > 650 RPM		
					Range_Disable is TRUE when any of the next three conditions are TRUE  Transmission Range is  Transmission Range is  Input Clutch is not -----	= Park ENUM  = Park/Reve rse Transiton al ENUM  = ON (Fully Applied) ENUM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Neutral_Speed_Enable is TRUE when All of the next three conditions are satisfied for	> 1.5 Seconds		
					Transmission Output Speed	> 130 RPM		
					The loop to loop change of the Transmission Output Speed is	< 125 RPM		
					The loop to loop change of the Transmission Output Speed is	> -10 RPM		
					-----			
					Transmission_Range_Enable is TRUE when one of the next six conditions is TRUE			
					Transmission Range is	= Neutral ENUM		
					Transmission Range is	= Reverse/Neutral Transitional ENUM		
					Transmission Range is	= Neutral/Drive Transitional ENUM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Time since a driven range (R,D) has been selected  Transmission Output Speed Sensor Raw Speed  Output Speed when a fault was detected	Table Based Time Please Refer to Table 21 in supporting documents  >= 500 RPM  >= 500 RPM		
					<b>Disable Condition s:</b>  <b>MIL not Illuminated for DTC's:</b>	TCM: P0973, P0974, P0976, P0977  ECM: P0101, P0102, P0103, P0121, P0122, P0123		
Torque Converter Clutch (TCC)	P0741	TCC System Stuck OFF	TCC Pressure  Either Condition (A) or (B) Must be Met  (A) TCC Slip Error @ TCC On Mode	>= 300 Kpa  >= RPM			>= 2 Enable Time (Sec)  >= 5 Fail Time (Sec)	Two Trips

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			(B) TCC Slip @ Lock On Mode	>= 130 RPM			>= 5 Fail Time (Sec)	
			If Above Conditions Have been Met, and Fail Timer Expired, Increment Fail Counter				>= 2 TCC Stuck Off Fail Counter	
					TCC Mode	= On or Lock		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed	>= 400 RPM		
					Engine Speed	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Engine Torque Lo	>= 30 N*m		
					Engine Torque Hi	<= 8191.875 N*m		
					Throttle Position Lo	>= 8.000183 Pct		
					Throttle Position Hi	<= 99.99847 Pct		
					2nd Gear Ratio Lo	>= 2.70459 Ratio		
					2nd Gear Ratio High	<= 3.111816 Ratio		
					3rd Gear Ratio Lo	>= 1.760132 Ratio		
					3rd Gear Ratio High	<= 2.025024 Ratio		
					4th Gear Ratio Lo	>= 1.345093 Ratio		
					4th Gear Ratio High	<= 1.547485 Ratio		
					5th Gear Ratio Lo	>= 0.930054 Ratio		
					5th Gear Ratio Hi	<= 1.069946 Ratio		
					6th Gear Ratio Lo	>= 0.693848 Ratio		
					6th Gear Ratio High	<= 0.79834 Ratio		
					Transmission Fluid Temperature Lo	>= -6.65625 °C		
					Transmission Fluid Temperature Hi	<= 130 °C		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					PTO Not Active Engine Torque Signal Valid Throttle Position Signal Valid Dynamic Mode P0741 Status is	= Vrai Boolean = Vrai Boolean = Vrai Boolean = Faux Boolean ≠ Test Failed This Key On or Fault Active		
					<b>Disa ble Condi tion s:</b>	<b>MIL not Illuminated for DTC's:</b> TCM: P0716, P0717, P0722, P0723, P0742, P2763, P2764  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Torque Converter Clutch (TCC)	P0742	TCC System Stuck ON	TCC Slip Speed TCC Slip Speed	>= -50 RPM <= 30 RPM			>= 1 Fail Time (Sec)	One Trip



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Above Conditions Have been Met, and Fail Timer Expired, Increment Fail Counter				>= 8 Fail Counter	
					TCC Mode	= Off		
					Enable test if Cmnd Gear = 1stFW and value true	= 1 Boolean		
					Enable test if Cmnd Gear = 2nd and value true	= 0 Boolean		
					Engine Speed Hi	<= 6000 RPM		
					Engine Speed Lo	>= 500 RPM		
					Vehicle Speed Hi	<= 511 KPH		
					Vehicle Speed Lo	>= 1 KPH		
					Engine Torque Hi	<= 8191.875 Nm		
					Engine Torque Lo	>= 30 Nm		
					Current Range	≠ Neutral Range		
					Current Range	≠ Reverse Range		
					Transmission Sump Temperature	<= 130 °C		
					Transmission Sump Temperature	>= 15 °C		
					Throttle Position Hyst High	>= 10.00061 Pct		
					AND			
					Max Vehicle Speed to Meet Throttle Enable	<= 8 KPH		
					Once Hyst High has been met, the enable will remain while Throttle Position	>= 2.000427 Pct		
					Disable for Throttle Position	>= 75 Pct		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disable if PTO active and value true	= 1 Boolean		
					Disable if in D1 and value true	= 1 Boolean		
					Disable if in D2 and value true	= 1 Boolean		
					Disable if in D3 and value true	= 1 Boolean		
					Disable if in D4 and value true	= 1 Boolean		
					Disable if in D5 and value true	= 1 Boolean		
					Disable if in MUMD and value true	= 1 Boolean		
					Disable if in TUTD and value true	= 1 Boolean		
					4 Wheel Drive Low Active	= Faux Boolean		
					Disable if Air Purge active and value false	= 0 Boolean		
					RVT Diagnostic Active	= Faux Boolean		
					Ignition Voltage	>= 9 V		
					Ignition Voltage	<= 31.99023 V		
					Vehicle Speed	<= 511 KPH		
					Engine Speed	>= 400 RPM		
					Engine Speed	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Engine Torque Signal Valid	= Vrai Boolean		
					Throttle Position Signal Valid	= Vrai Boolean		
					P0742 Status is	≠ Test Failed This Key On or Fault Active		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P0741, P2763, P2764  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Mode 2 Multiplex Valve	P0751	Shift Solenoid Valve A Stuck Off	Commaned Gear Slip  Commanded Gear  Gear Ratio  Gear Ratio  If the above parameters are true	>= 400 RPM  = 1st Lock rpm  <= 1.5474854  >= 1.3450928			>= 0.3 Fail Tmr  = 5 Fail Counts  ≠ 0 Neutral Timer (Sec)  >= 0.3 Fail Timer (Sec)  >= 8 Counts	Two Trips
					Ignition Voltage Lo Ignition Voltage Hi Engine Speed Lo Engine Speed Hi	>= 9 Volts <= 31.99023 Volts >= 400 RPM <= 7500 RPM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Transmission Fluid Temperature	>= -6.65625 °C		
					Range Shift State	= Range Shift Completed ENUM		
					TPS	>= 0.500488 %		
					OR			
					Output Speed	>= 110 RPM		
					Throttle Position Signal Valid from ECM	= Vrai Boolean		
					Engine Torque Signal Valid from ECM, High side driver is enabled	= Vrai Boolean		
					High-Side Driver is Enabled	= Vrai Boolean		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Default Gear Option is not present	= Vrai		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					<p>Disa ble Con diti on s:</p> <p>MIL not Illuminated for DTC's:</p>	<p>TCM: P0716, P0717, P0722, P0723, P182E</p> <p>ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E</p>		
Mode 2 Multiplex Valve	P0752	Shift Solenoid Valve A Stuck On	<p>Gear Box Slip</p> <p>Commanded Gear</p> <p>Commanded Gear has Achieved 1st Locked OR 1st Free Wheel OR 2nd with Mode 2 Sol. Commanded On</p> <p>If the above parameters are true</p>	<p>&gt;= 400 RPM</p> <p>= 3rd Gear</p> <p>= Vrai Boolean</p>				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Command 4th Gear once Output Shaft Speed	<= 1000 RPM			Please Refer to Table Neutral >= 16 in Timer Supporting (Sec) Documents	
			If Gear Ratio	>= 4.1378174			>= 1.5 Fail Timer (Sec)	
			And Gear Ratio	<= 4.7606201			>= 5 Counts	
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					High-Side Driver is Enabled	= Vrai Boolean		
					Throttle Position Signal Valid from ECM	= Vrai Boolean		
					Output Speed	>= 110 RPM		
					OR TPS	>= 0.500488 %		
					Range Shift State	= Range Shift Completed ENUM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Transmission Fluid Temperature Input Speed Sensor fault Output Speed Sensor fault Default Gear Option is not present	>= -6.65625 °C = Faux Boolean = Faux Boolean = Vrai		
					Disable Condition s: MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P0776	Pressure Control (PC) Solenoid B Stuck Off [C35R]	<u>Fail Case 1</u> Case: Steady State 3rd Gear		Commanded Gear = 3rd Gear Gearbox Slip >= 400 RPM			One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>Command 4th Gear once Output Shaft Speed</p> <p>If Gear Ratio And Gear Ratio</p> <p>It the above condiations are true, Increment 3rd gear fail counter</p> <p>and C35R Fail counter</p>	<p>&lt;= 1000 RPM</p> <p>&gt;= 1.3450928</p> <p>&lt;= 1.5474854</p>			<p>Please Refer to Table Neutral &gt;= 16 in Timer Suppo (Sec) rting Docu ments</p> <p>&gt;= 3 Fail Timer (Sec)</p> <p>&gt;= 2 3rd Gear Fail Counts</p> <p>or</p> <p>&gt;= 14 3-5R Clutch Fail Counts</p>	
			<p><u>Fail</u> Case: Steady State <u>Case 2</u> 5th Gear</p> <p>Commanded Gear</p>	<p>= 5th Gear</p>				



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Gearbox Slip	>= 400 Rpm			Please Refer to Table Neutral >= 5 in Timer (Sec) Supporting Documents	
			Intrusive Test: Command 6th Gear					
			If attained Gear=6th gear Time	>= Please refer to Shift Table 3 in Time supporting documents (Sec)				
			It the above condiations are true, Increment 5th gear fail counter				>= 3 5th Gear Fail Counts	
			and C35R Fail counter				>= 14 3-5R Clutch Fail Counts	
					PRNDL State defaulted	= Faux Boolean		
					inhibit RVT	= Faux Boolean		
					IMS fault pending indication	= Faux Boolean		
					TPS validity flag	= Vrai Boolean		
					Hydraulic System Pressurized	= Vrai Boolean		
					Minimum output speed for RVT	>= 110 RPM		
					A OR B			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					(A) Output speed enable	>= 110 RPM		
					(B) Accelerator Pedal enable	>= 0.500488 Pct		
					Common Enable Criteria			
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Throttle Position Signal valid	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		
					Transmission Fluid Temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Default Gear Option is not present	= Vrai		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P0777	Pressure Control (PC) Solinoid B Stuck On [C35R] (Steady State)	<p><u>Fail</u> <u>Case 1</u> Case: Steady State 1st</p> <p>Attained Gear slip &gt;= 400 RPM</p> <p>If the Above is True for Time &gt;= Please Refer to Table 4 in supporting documents</p> <p>Intrusive test: (CBR1 clutch exhausted)</p> <p>Gear Ratio &lt;= 2.0250244</p> <p>Gear Ratio &gt;= 1.7601318</p> <p>If the above parameters are true</p>					One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
							>= 1.1 Fail Timer (Sec)  >= 2 Fail Count in 1st Gear  or  >= 3 Total Fail Counts	
			<u>Fail</u> Case: Steady State <u>Case 2</u> 2nd gear	Table Based value Please rpm/s => Refer to 3D ec Table 1 in supporting documents				
			Min Delta Output Speed Hysteresis	Table Based value Please rpm/s => Refer to 3D ec Table 2 in supporting documents				
			If the Above is True for Time	Table Based Time Please Sec => Refer to Table 17 in supporting documents				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Intrusive test: (CB26 clutch exhausted)  Gear Ratio <= 2.0250244 Gear Ratio >= 1.7601318  If the above parameters are true				>= 1.1 Fail Timer (Sec)  >= 3 Fail Count in 2nd Gear  or  >= 3 Total Fail Counts	
			<u>Fail Case 3</u> Case: Steady State 4th gear					
			Max Delta Output Speed Hysteresis	Table Based value Please Refer to 3D Table 1 in supporting documents	>= rpm/s ec			
			Min Delta Output Speed Hysteresis	Table Based value Please Refer to 3D Table 2 in supporting documents	>= rpm/s ec			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>If the Above is True for Time</p> <p>Intrusive test: (C1234 clutch exhausted)</p> <p>Gear Ratio</p> <p>Gear Ratio</p> <p>If the above parameters are true</p>	<p>Table Based Time</p> <p>&gt;= Please Refer to Table 17 in supporting documents</p> <p>Sec</p> <p>&lt;= 1.0699463</p> <p>&gt;= 0.9300537</p>			<p>&gt;= 1.1 Fail Timer (Sec)</p> <p>&gt;= 3 Fail Count in 4th Gear</p> <p>or</p> <p>&gt;= 3 Total Fail Counts</p>	
			<p><u>Fail</u> <u>Case 4</u> Case: Steady State 6th gear</p> <p>Max Delta Output Speed Hysteresis</p>	<p>Table Based value</p> <p>&gt;= Please Refer to 3D ec Table 1 in supporting documents</p> <p>rpm/s</p>				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Min Delta Output Speed Hysteresis	>=	Table Based value Please rpm/s Refer to 3D ec Table 2 in supporting documents			
			If the Above is True for Time	>=	Table Based Time Please Sec Refer to Table 17 in supporting documents			
			Intrusive test: (CB26 clutch exhausted)					
			Gear Ratio	<=	1.0699463		>= 1.1	Fail Timer (Sec)
			Gear Ratio	>=	0.9300537		>= 3	counts
			If the above parameters are true				>= 1.1	Fail Timer (Sec)
							>= 3	Fail Count in 6th Gear or Total Fail Counts
					PRNDL State defaulted	= Faux Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					inhibit RVT	= Faux Boolean		
					IMS fault pending indication	= Faux Boolean		
					output speed	>= 0 RPM		
					TPS validity flag	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		
					Hydraulic_System_Pre ssurized	= Vrai Boolean		
					A OR B			
					(A) Output speed enable	>= 110 Nm		
					(B) Accelerator Pedal enable	>= 0.500488 Nm		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					if Attained Gear=1st FW Accelerator Pedal enable	>= 10.00061 Pct		
					if Attained Gear=1st FW Engine Torque Enable	>= 45 Nm		
					if Attained Gear=1st FW Engine Torque Enable	<= 8191.875 Nm		
					Transmission Fluid Temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P0777	Pressure Control (PC) Solenoid B StuckOn [C35R] (Dymanic)	Primary Offgoing Clutch is exhausted (See Table 12 in Supporting Documents for Exhaust Delay Timers)  Primary Oncoming Clutch Pressure Command Status  Primary Offgoing Clutch Pressure Command Status  Range Shift Status  Attained Gear Slip	=  =  =  ≠  <=	Vrai  Boolean  Maximum pressurized  Clutch exhaust command  Initial Clutch Control  40 RPM			One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If the above conditions are true run appropriate Fail 1 Timers Below:					
			fail timer 1 (3-1 shifting with Closed Throttle)	>= 0.5				
			fail timer 1 (3-2 shifting with Throttle)	>= 0.4003906				
			fail timer 1 (3-2 shifting with Closed Throttle)	>= 0.5				
			fail timer 1 (3-4 shifting with Throttle)	>= 0.4003906				
			fail timer 1 (3-4shifting with Closed Throttle)	>= 0.5				
			fail timer 1 (3-5 shifting with Throttle)	>= 0.4003906				
			fail timer 1 (3-5 shifting with Closed Throttle)	>= 0.5				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			fail timer 1 (5-3 shifting with Throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (5-3 shifting with Closed Throttle)	>= 0.5	Fail Time (Sec)			
			fail timer 1 (5-4 shifting with Throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (5-4 shifting with Closed Throttle)	>= 0.5	Fail Time (Sec)			
			fail timer 1 (5-6 shifting with Throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (5-6 shifting with Closed Throttle)	>= 0.5	Fail Time (Sec)			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Attained Gear Slip is Less than Above Cal Increment Fail Timers				Total Fail Time = (Fail 1 + Fail 2) See Enabl e Timers for Fail >= Timer    sec 1, and Refere nce Suppo rting Table 15 for Fail Timer 2	
			If fail timer is greater than threshold increment corresponding gear fail counter and total fail counter					
			3rd gear fail counter				>= 3    3rd gear fail counts OR	
			5th gear fail counter				>= 3    5th gear fail counts OR	
			Total fail counter				>= 3    total fail counts	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					TUT Enable temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Command / Attained Gear	≠ 1st Boolean		
					High Side Driver ON	= Vrai Boolean		
					output speed limit for TUT	>= 200 RPM		
					input speed limit for TUT	>= 200 RPM		
					PRNDL state defaulted	= Faux Boolean		
					IMS Fault Pending	= Faux Boolean		
					Service Fast Learn Mode	= Faux Boolean		
					HSD Enabled	= Vrai Boolean		
					Default Gear Option is not present	= Vrai		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Transmission Output Speed Sensor (TOSS)	P077C	Output Speed Sensor Circuit Low	TOSS Analog Signal Voltage	<= 0.25 Volts			>= ##### sec	One Trip
			P077C Status is not	= Test Failed This Key On or Fault Active				
			If the above conditons have been met, increment the P077C Fail Counter					
			DTC P077C Sets when the Fail Counter	>= 75 Coun ts				
					P077C Enable Calibration	= 1 Boolean		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not Illuminated for DTC's:	TCM: P077D		
Transmission Output Speed Sensor (TOSS)	P077D	Output Speed Sensor Circuit High	TOSS Analog Signal Voltage	>= 4.75 Volts	Test Failed This Key On or Fault Active		>= ##### sec	One Trip
			P077D Status is not	=				
			DTC P077D Sets when the Fail Counter	>= 75 Coun ts	Disa ble Con diti on s:  MIL not Illuminated for DTC's:	P077D Enable Calibration = 1 Boolean Ignition Voltage Lo >= 9 Volts Ignition Voltage Hi <= 31.99023 Volts  TCM: P077C		
Variable Bleed Solenoid (VBS)	P0796	Pressure Control (PC) Solenoid C Stuck Off [C456] (Steady State)	<u>Fail</u> <u>Case 1</u> Case: Steady State 4th Gear					One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Gear slip	>= 400 RPM			Please See Table Neutral >= 5 For Timer Neutra (Sec) I Time Cal	
			Intrusive test: commanded 5th gear					
			If attained Gear ≠5th for time	>=	Please refer to Shift Table 3 in Time Supporting (Sec) Documents			
			if the above conditions have been met					
			Increment 4th Gear Fail Counter				>= 2	4th Gear Fail Count
			and C456 Fail Counters				>= 14	OR C456 Fail Counts
			<u>Fail Case 2</u> Case: Steady State 5th Gear					
			Gear slip	>= 400 RPM			Please See Table Neutral >= 5 For Timer Neutra (Sec) I Time Cal	



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>Intrusive test: commanded 6th gear</p> <p>If attained Gear ≠ 6th for time</p> <p>if the above conditions have been met</p> <p>Increment 5th Gear Fail Counter</p> <p>and C456 Fail Counters</p>	<p>≥</p> <p>Please Refer to Shift Table 3 in Time Supporting (Sec) Documents</p>			<p>≥ 2</p> <p>5th Gear Fail Count  OR  C456 Fail Counts</p> <p>≥ 14</p>	
			<p><u>Fail</u> <u>Case 3</u> Case: Steady State 6th Gear</p> <p>Gear slip</p> <p>Intrusive test: commanded 5th gear</p> <p>If attained Gear ≠ 5th for time</p>	<p>≥</p> <p>400 RPM</p> <p>≥</p> <p>Please refer to Shift Table 3 in Time Supporting (Sec) Documents</p>			<p>≥</p> <p>Please See Table Neutral 5 For Timer Neutra (Sec) I Time Cal</p>	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			if the above conditions have been met  Increment 6th Gear Fail Counter and C456 Fail Counter  and C456 Fail Counter				>= 2  6th Gear Fail Count  OR  >= 14  C456 Fail Counts	
					PRNDL State defaulted	= Faux Boolean		
					inhibit RVT	= Faux Boolean		
					IMS fault pending indication	= Faux Boolean		
					TPS validity flag	= Vrai Boolean		
					Hydraulic System Pressurized	= Vrai Boolean		
					Minimum output speed for RVT	>= 110 RPM		
					A OR B			
					(A) Output speed enable	>= 110 RPM		
					(B) Accelerator Pedal enable	>= 0.500488 Pct		
					Common Enable Criteria			
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Throttle Position Signal valid	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Transmission Fluid Temperature Input Speed Sensor fault OutputSpeed Sensor fault Default Gear Option is not present  <b>MIL not Illuminated for DTC's:</b>	>= -6.65625 °C = Faux Boolean = Faux Boolean = Vrai  TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P0797	Pressure Control (PC) Solenoid C Stuck On [C456] (Steady State)	<u>Fail Case 1</u> Case: Steady State 1st  Attained Gear slip	>= 400 RPM				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>If the Above is True for Time</p> <p>Intrusive test: (CBR1 clutch exhausted)</p> <p>Gear Ratio</p> <p>Gear Ratio</p> <p>If the above parameters are true</p>	<p>Table Based Time    Enab Please    le Refer to Time Table 4 in (Sec) supporting documents</p> <p>&lt;= 1.5474854</p> <p>&gt;= 1.3450928</p>			<p>&gt;= 1.1    Fail Timer (Sec)</p> <p>&gt;= 2    Fail Count in 1st Gear</p> <p>or</p> <p>&gt;= 3    Total Fail Counts</p>	
			<p><u>Fail</u> <u>Case 2</u>    Case Steady State 2nd</p> <p>Max Delta Output Speed Hysteresis</p>	<p>Table Based value</p> <p>&gt;=    Please    rpm/s Refer to 3D ec Table 1 in supporting documents</p>				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Min Delta Output Speed Hysteresis	<p>Table Based value Please Refer to 3D ec Table 2 in supporting documents</p> <p>&gt;= rpm/s</p>				
			If the Above is True for Time	<p>Table Based Time Please Refer to Table 17 in supporting documents</p> <p>&gt;= Sec</p>				
			Intrusive test: (CB26 clutch exhausted)					
			Gear Ratio	<= 1.5474854				
			Gear Ratio	>= 1.3450928				
			If the above parameters are true				<p>&gt;= 1.1 Fail Timer (Sec)</p> <p>&gt;= 3 Fail Count in 2nd Gear</p> <p>or</p> <p>&gt;= 3 Total fail counts</p>	
			Fail Case 3	Case Steady State 3rd				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Max Delta Output Speed Hysteresis	Table Based value Please rpm/s Refer to 3D ec Table 1 in supporting documents >=				
			Min Delta Output Speed Hysteresis	Table Based value Please rpm/s Refer to 3D ec Table 2 in supporting documents >=				
			If the Above is True for Time	Table Based Time Please Sec Refer to Table 17 in supporting documents >=				
			Intrusive test: (C35R clutch exhausted)					
			Gear Ratio	<= 1.5474854				
			Gear Ratio	>= 1.3450928				
			If the above parameters are true				>= 1.1	Fail Timer (Sec)
							>= 3	Fail Count in 3rd Gear

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
							OR >= 3 Total Fail Counts	
					PRNDL State defaulted	= Faux Boolean		
					inhibit RVT	= Faux Boolean		
					IMS fault pending indication	= Faux Boolean		
					output speed	>= 0 RPM		
					TPS validity flag	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		
					Hydraulic_System_Pre ssurized	= Vrai Boolean		
					A OR B			
					(A) Output speed enable	>= 110 Nm		
					(B) Accelerator Pedal enable	>= 0.500488 Nm		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					if Attained Gear=1st FW Accelerator Pedal enable	>= 10.00061 Pct		
					if Attained Gear=1st FW Engine Torque Enable	>= 45 Nm		
					if Attained Gear=1st FW Engine Torque Enable	<= 8191.875 Nm		
					Transmission Fluid Temperature	>= -6.65625 °C		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Input Speed Sensor fault Output Speed Sensor fault Default Gear Option is not present  <b>MIL not Illuminated for DTC's:</b>	= Faux Boolean = Faux Boolean = Vrai  TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P0797	Pressure Control (PC) Solenoid C Stuck On [C456] (Dynamic)	Primary Offgoing Clutch is exhausted (See Table 11 in Supporting Documents for Exhaust Delay Timers)  Primary Oncoming Clutch Pressure Command Status  Primary Offgoing Clutch Pressure Command Status	= Vrai Boolean  = Maximum pressurized  = Clutch exhaust command				One Trip



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Range Shift Status	≠ Initial Clutch Control				
			Attained Gear Slip	≤ 40 RPM				
			If the above conditions are true increment appropriate Fail 1 Timers Below:					
			fail timer 1 (4-1 shifting with throttle)	≥ 0.4003906	Fail Time (Sec)			
			fail timer 1 (4-1 shifting without throttle)	≥ 0.5	Fail Time (Sec)			
			fail timer 1 (4-2 shifting with throttle)	≥ 0.4003906	Fail Time (Sec)			
			fail timer 1 (4-2 shifting without throttle)	≥ 0.5	Fail Time (Sec)			
			fail timer 1 (4-3 shifting with throttle)	≥ 0.4003906	Fail Time (Sec)			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			fail timer 1 (4-3 shifting without throttle)	>= 0.5	Fail Time (Sec)			
			fail timer 1 (5-3 shifting with throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (5-3 shifting without throttle)	>= 0.5	Fail Time (Sec)			
			fail timer 1 (6-2 shifting with throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (6-2 shifting without throttle)	>= 0.5	Fail Time (Sec)			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Attained Gear Slip is Less than Above Cal Increment Fail Timers				Total Fail Time = (Fail 1 + Fail 2) See Enabl e Timers for Fail >= Timer    sec 1, and Refere nce Suppo rting Table 15 for Fail Timer 2	
			If fail timer is greater than threshold increment corresponding gear fail counter and total fail counter					
			4th gear fail counter				Fail Counter >= 3    From 4th Gear OR	
			5th gear fail counter				Fail Counter >= 3    From 5th Gear	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			6th gear fail counter				OR Fail Counter From 6th Gear >= 3	
			Total fail counter				OR Total Fail Counter >= 3	
					TUT Enable temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Command / Attained Gear	≠ 1st Boolean		
					High Side Driver ON	= Vrai Boolean		
					output speed limit for TUT	>= 200 RPM		
					input speed limit for TUT	>= 200 RPM		
					PRNDL state defaulted	= Faux Boolean		
					IMS Fault Pending	= Faux Boolean		
					Service Fast Learn Mode	= Faux Boolean		
					HSD Enabled	= Vrai Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Transmission Input Speed Sensor (TISS)	P07BF	Input/Turbine Speed Sensor A Circuit Low	TISS Analog Signal Voltage	<= 0.25 Volts			>= ##### sec	One Trip
			P07BF Status is not	=  Test Failed This Key On or Fault Active				
			If the above conditons have been met, increment the P07BF Fail Counter					
			DTC P07BF Sets when the Fail Counter	>= 75 Coun ts	P07BF Enable Calibration	= 1 Boolean		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:			
Transmission Input Speed Sensor (TISS)	P07C0	Input/Turbine Speed Sensor A Circuit High	TISS Analog Signal Voltage	>= 4.75 Volts	MIL not Illuminated for DTC's:		>= ##### sec	One Trip
			P07C0 Status is not	= Test Failed This Key On or Fault Active				
			If the above conditons have been met, increment the P07C0 Fail Counter					
			DTC P07C0 Sets when the Fail Counter	>= 75 Coun ts	Disa ble Con diti on s:	P07C0 Enable Calibration = 1 Boolean		
						Ignition Voltage Lo >= 9 Volts Ignition Voltage Hi <= 31.99023 Volts		
Tap Up Tap Down Switch (TUTD)	P0815	Upshift Switch Circuit	<u>Fail</u> <u>Case 1</u> Tap Up Switch Stuck in the Up Position in Range 1 Enabled	= 1 Bool ean	MIL not Illuminated for DTC's:			Special No MIL

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Tap Up Switch Stuck in the Up Position in Range 2 Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Range 3 Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Range 4 Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Range 5 Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Range 6 Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Neutral Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Park Enabled	= 1 Boolean				
			Tap Up Switch Stuck in the Up Position in Reverse Enabled	= 1 Boolean				
			Tap Up Switch ON	= Vrai Boolean			>= 1 Fail Time (Sec)	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<u>Fail Case 2</u> Tap Up Switch Stuck in the Up Position in Range 1 Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Range 2 Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Range 3 Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Range 4 Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Range 5 Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Range 6 Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Neutral Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Park Enabled	= 1	Boolean			
			Tap Up Switch Stuck in the Up Position in Reverse Enabled	= 1	Boolean			
			Tap Up Switch ON	= Vrai	Boolean			



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			NOTE: Both Failcase1 and Failcase 2 Must Be Met				>= 600 Fail Time (Sec)	
					Time Since Last Range Change	>= 1 Enable Time (Sec)		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					P0815 Status is	Test Failed This Key On or Fault Active		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:	MIL not Illuminated for DTC's: TCM: P0816, P0826, P182E, P1876, P1877, P1915, P1761  ECM: None		
Tap Up Tap Down Switch (TUTD)	P0816	Downshift Switch Circuit	<u>Fail Case 1</u> Tap Down Switch Stuck in the Down Position in Range 1 Enabled	= 1	Bool ean			Special No MIL
			Tap Down Switch Stuck in the Down Position in Range 2 Enabled	= 1	Bool ean			
			Tap Down Switch Stuck in the Down Position in Range 3 Enabled	= 1	Bool ean			
			Tap Down Switch Stuck in the Down Position in Range 4 Enabled	= 1	Bool ean			
			Tap Down Switch Stuck in the Down Position in Range 5 Enabled	= 1	Bool ean			
			Tap Down Switch Stuck in the Down Position in Range 6 Enabled	= 1	Bool ean			
			Tap Down Switch Stuck in the Down Position in Range Neutral Enabled	= 1	Bool ean			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Tap Down Switch Stuck in the Down Position in Range Park Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Range Reverse Enabled	= 1 Boolean				
			Tap Down Switch ON	= Vrai Boolean			>= 1 sec	
		<u>Fail Case 2</u>	Tap Down Switch Stuck in the Down Position in Range 1 Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Range 2 Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Range 3 Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Range 4 Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Range 5 Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Range 6 Enabled	= 1 Boolean				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Tap Down Switch Stuck in the Down Position in Neutral Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Park Enabled	= 1 Boolean				
			Tap Down Switch Stuck in the Down Position in Reverse Enabled	= 1 Boolean				
			Tap Down Switch ON	= Vrai Boolean				
			NOTE: Both Failcase1 and Failcase 2 Must Be Met				>= 600 sec	
					Time Since Last Range Change	>= 1 Enable Time (Sec)		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed is within the allowable limits for  P0816 Status is	>= 5 Sec  Test Failed This Key On or Fault Active		
					<b>Disa ble Con diti on s:</b>  <b>MIL not Illuminated for DTC's:</b>	TCM: P0815, P0826, P182E, P1876, P1877, P1915, P1761  ECM: None		
Tap Up Tap Down Switch (TUTD)	P0826	Up and Down Shift Switch Circuit	TUTD Circuit Reads Invalid Voltage	= Vrai Bool ean			>= 60 Fail Time (Sec)	Special No MIL
					Ignition Voltage Lo Ignition Voltage Hi Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for  P0826 Status is	>= 9 Volts <= 31.99023 Volts >= 400 RPM <= 7500 RPM >= 5 Sec  Test Failed This Key On or Fault Active		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disable Condition s: MIL not Illuminated for DTC's:	TCM: P1761 ECM: None		
Variable Bleed Solenoid (VBS)	P0961	Pressure Control (PC) Solenoid A Control Circuit Rationality Test (Line Pressure VRS)	The HWIO reports an invalid voltage (out of range) error flag	= Vrai Boolean			>= 4.4 Fail Time (Sec)  out of 5 Sample Time (Sec)	Two Trips
Variable Bleed Solenoid (VBS)	P0962	Pressure Control (PC) Solenoid A Control Circuit Low Voltage (Line Pressure VRS)	The HWIO reports a low voltage (ground short) error flag	= Vrai Boolean			>= 1.5 Fail Time (Sec)  out of 1.875 Sample Time (Sec)	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed Engine Speed is within the allowable limits for	<= 7500 RPM >= 5 Sec		
					<b>Disa ble Con diti on s:</b> <b>MIL not Illuminated for DTC's:</b>	TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P0963	Pressure Control (PC) Solenoid A Control Circuit High Voltage (Line Pressure VRS)	The HWIO reports a high voltage (open or power short) error flag	= Vrai Bool ean			>= 4.4 Fail Time (Sec)	Two Trips
							out of 5 Sample Time (Sec)	
					Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec	TCM: None ECM: None		
					<b>Disa ble Con diti on s:</b> <b>MIL not Illuminated for DTC's:</b>	TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P0966	Pressure Control (PC) Solenoid B Control Circuit Low Voltage (C35R VBS)	The HWIO reports a low voltage (ground short) error flag	= Vrai Bool ean			>= 0.3 Fail Time (Sec)	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
							out of 0.375 Sample Time (Sec)	
					Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec P0966 Status is not = Test Failed This Key On or Fault Active			
					<b>Disa ble Con diti on s:</b>	<b>MIL not Illuminated for DTC's:</b> TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P0967	Pressure Control (PC) Solenoid B Control Circuit High Voltage (C35R VBS)	The HWIO reports a high voltage (open or power short) error flag	= Vrai Boolean			>= 0.3 Fail Time (Sec) out of 0.375 Sample Time (Sec)	One Trip
					Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec			



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					P0967 Status is not	Test Failed = This Key On or Fault Active  MIL not Illuminated for DTC's: TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P0970	Pressure Control (PC) Solenoid C Control Circuit Low Voltage (C456/CBR1 VBS)	The HWIO reports a low voltage (ground short) error flag	= Vrai Boolean			>= 0.3 Fail Time (Sec)	One Trip
							out of 0.375 Sample Time (Sec)	
					P0970 Status is not	Test Failed = This Key On or Fault Active  Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P0971	Pressure Control (PC) Solenoid C Control Circuit High Voltage (C456/CBR1 VBS)	The HWIO reports a high voltage (open or power short) error flag	= Vrai Bool ean			>= 0.3 Fail Time (Sec)  out of 0.375 Sample Time (Sec)	One Trip
						Test Failed This Key On or Fault Active  Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec		
					Disa ble Con diti on s:  MIL not illuminated for DTC's:	TCM: None ECM: None		
Shift Solinoid	P0973	Shift Solenoid A Control Circuit Low (Mode 2 Solenoid)	The HWIO reports a low voltage (ground short) error flag	= Vrai Bool ean			>= 1.2 Fail Time (Sec)	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
							out of 1.5 Sample Time (Sec)	
					P0973 Status is not	= Test Failed This Key On or Fault Active		
					Ignition Voltage	>= 9 Volts		
					Ignition Voltage	<= 31.99023 Volts		
					Engine Speed	>= 400 RPM		
					Engine Speed	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
				Disa ble Con diti on s:	MIL not illuminated for DTC's:	TCM: None ECM: None		
Shift Solenoid	P0974	Shift Solenoid A Control Circuit High (Mode 2 Solenoid)	The HWIO reports a high voltage (open or power short) error flag	= Vrai Boolean			>= 1.2 Fail Time (Sec)	Two Trips
							out of 1.5 Sample Time (Sec)	
					P0974 Status is not	= Test Failed This Key On or Fault Active		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec	MIL not Illuminated for DTC's: TCM: None ECM: None		
Tap Up Tap Down Switch (TUTD)	P1761	Tap Up and Down switch signal circuit (rolling count)	Rolling count value received from BCM does not match expected value	= Vrai Boolean			>= 3 Fail Counter > 10 Sample Timer (Sec)	Special No MIL
					Tap Up Tap Down Message Health = Vrai Boolean Engine Speed Lo >= 400 RPM Engine Speed Hi <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec	MIL not Illuminated for DTC's: TCM: None ECM: None		
Internal Mode Switch (IMS)	P182E	Internal Mode Switch - Invalid Range	<u>Fail Case 1</u> Current range	= Transition 1 (bit state 1110) Range				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Previous range	≠ CeTRGR_e _PRNDL_D Rang rive6 e				
			Previous range	≠ CeTRGR_e _PRNDL_D Rang rive5 e				
			Range Shift State	= Range Shift ENU Completed M				
			Absolute Attained Gear Slip	<= 50 rpm				
			Attained Gear	<= Sixth				
			Attained Gear	>= First				
			Throttle Position Available	= Vrai				
			Throttle Position	>= 8.0001831 pct				
			Output Speed	>= 200 rpm				
			Engine Torque	>= 50 Nm				
			Engine Torque	<= 8191.75 Nm				
			If the above conditions are met then Increment Fail Timer				>= 1 Seconds	
			If Fail Timer has Expired then Increment Fail Counter				>= 5 Fail Counts	
			<u>Fail Case 2</u>					
			Output Speed	<= 70 rpm				
			The following PRNDL sequence events occur in this exact order:					
			PRNDL state	= Drive 6 (bit Rang state 0110) e				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			PRNDL state = Drive 6 for	>= 1 Sec				
			PRNDL state =	Transition 8 (bit state 0111) Range				
			PRNDL state =	Drive 6 (bit state 0110) Range				
			PRNDL state =	Transition 1 (bit state 1110) Range				
			Above sequencing occurs in	<= 1 Sec				
			Neutral Idle Mode =	Inactive				
			If all conditions above are met Increment delay Timer					
			If the below two conditions are met Increment Fail Timer				>= 3	Fail Seconds
			delay timer	>= 1 Sec				
			Input Speed	>= 400 Sec				
			If Fail Timer has Expired then Increment Fail Counter				>= 2	Fail Counts
		<u>Fail Case 3</u>	Current range =	Transition 13 (bit state 0010) Range	Previous range	CeTRGR_e_PRNDL_Drive5 ≠		
			Engine Torque	>= -8192 Nm	Previous range	CeTRGR_e_PRNDL_Drive5 ≠		
			Engine Torque	<= 8191.75 Nm	IMS is 7 position configuration	= 0 Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>If the above conditions are met then, Increment Fail Timer</p> <p>If Fail Timer has Expired then Increment Fail Counter</p>		<p>If the "IMS 7 Position config" = 1 then the "previous range" criteria above must also be satisfied when the "current range" = "Transition 13"</p>		<p>&gt;= 0.225 Seconds</p> <p>&gt;= 15 Fail Counts</p>	
			<p><u>Fail Case 4</u></p> <p>Current range = Transition 8 (bit state 0111) Range</p> <p>Inhibit bit (see definition) = Faux</p> <p>Steady State Engine Torque &gt;= 30 Nm</p> <p>Steady State Engine Torque &lt;= 8191.75 Nm</p> <p>If the above conditions are met then Increment Fail Timer</p> <p>If the above Conditions have been met, Increment Fail Counter</p>		<p>Disable Fail Case 4 if last positive range was Drive 6 and current range is transition 8</p> <p>Set inhibit bit true if PRNDL = 1100 (rev) or 0100 (Rev-Neu transition 11)</p> <p>Set inhibit bit false if PRNDL = 1001 (park)</p>		<p>&gt;= 0.225 Seconds</p> <p>&gt;= 15 Fail Counts</p>	
			<p><u>Fail Case 5</u></p> <p>Throttle Position Available = Vrai Boolean</p>					

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>The following PRNDL sequence events occur in this exact order:</p> <p>PRNDL State = Reverse (bit state 1100) Range</p> <p>PRNDL State = Transition 11 (bit state 0100) Range</p> <p>PRNDL State = Neutral (bit state 0101) Range</p> <p>PRNDL State = Transition 11 (bit state 0100) Range</p> <p>Above sequencing occurs in &lt;= 1 Sec</p> <p>Then delay timer increments</p> <p>Delay timer &gt;= 5 sec</p> <p>Range Shift State = Range Shift Complete</p> <p>Absolute Attained Gear Slip &lt;= 50 rpm</p> <p>Attained Gear &lt;= Sixth</p> <p>Attained Gear &gt;= First</p> <p>Throttle Position &gt;= 8.0001831 pct</p> <p>Output Speed &gt;= 200 rpm</p> <p>If the above conditions are met</p> <p>Increment Fail Timer</p>				>= 20 Seconds	
			<p><u>Fail Case 6</u></p> <p>Current range = Illegal (bit state 0000 or 1000 or 0001)</p>		A Open Circuit Definition (flag set false if the following conditions are met):			



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			and  A Open Circuit (See Definition)	= Faux Boolean	Current Range  Last positive state  Previous transition state  Fail case 5 delay timer	≠ Transition 11 (bit state 0100)  ≠ Neutral (bit state 0101)  ≠ Transition 8 (bit state 0111)  = 0 sec	>= 6.25 Seconds	
			<u>Fail Case 7</u>  Current PRNDL State  and  Previous PRNDL state  Input Speed  Reverse Trans Ratio  Reverse Trans Ratio	= PRNDL circuit Range ABCP = 1101  = PRNDL circuit Range ABCP = 1111  >= 150 RPM  <= 2.670166 ratio  >= 3.0720215 ratio				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If the above Conditions are met then, Increment Fail timer				>= 6.25 Seconds	
			P182E will report test fail when any of the above 7 fail cases are met			Ignition Voltage Lo >= 9 Volts Ignition Voltage Hi <= 31.99023 Volts Engine Speed Lo >= 400 RPM Engine Speed Hi <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec Engine Torque Signal Valid = Vrai Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P07C0, P07BF, P077C, P077D  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Tap Up Tap Down Switch (TUTD)	P1876	Tap Up and Down Enable Switch Circuit	Current range  TUTD Enable Switch is Active	= Park or Rang Reverse or e Neutral State  = Vrai Bool ean			>= 3 Fail Time (Sec)  >= 5 Fail Counts	Special No MIL
					Ignition Voltage Lo Ignition Voltage Hi Vehicle Speed Lo Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for	>= 9 Volts <= 31.99023 Volts <= 511 KPH >= 400 RPM <= 7500 RPM >= 5 Sec		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					P1876 Status is	≠ Test Failed This Key On or Fault Active		
					Disable Condition s: MIL not Illuminated for DTC's:	TCM: P0815, P0816, P0826, P1761, P1825, P1877, P1915, U0100 ECM: None		
Internal Mode Switch (IMS)	P1915	Internal Mode Switch Does Not Indicate Park/Neutral (P/N) During Start	PRNDL State is  The following events must occur Sequentially	≠ Park or Neutral Enumera tion				One Trip
			Initial Engine speed	≤= 50 RPM			≥= 0.1 Enable Time (Sec)	
			Then Engine Speed Between Following Cals					
			Engine Speed Lo Hist	≥= 50 RPM				
			Engine Speed Hi Hist	≤= 480 RPM			≥= 0.069 Enable Time (Sec)	
			Then					

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Final Engine Speed	>= 500 RPM				
			Final Transmission Input Speed	>= 100 RPM			>= 1.25	Fail Time (Sec)
					DTC has Ran this Key Cycle?	= Faux Boolean		
					Ignition Voltage Lo	>= 6 V		
					Ignition Voltage Hi	<= 31.99023 V		
					Ignition Voltage Hyst High (enables above this value)	>= 5 V		
					Ignition Voltage Hyst Low (disabled below this value)	<= 2 V		
					Transmission Output Speed	<= 90 rpm		
					P1915 Status is	≠ Test Failed This Key On or Fault Active		
					<b>Disa ble Cond ition s:</b>	<b>MIL not Illuminated for DTC's:</b>	TCM: P0722, P0723 ECM: None	
Transmission Control Module (TCM)	P2534	Ignition Switch Run/Start Position Circuit Low	TCM Run crank active (based on voltage thresholds below)	= Faux Bool ean				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Ignition Voltage High Hyst (run crank goes true when above this value)	5 Volts			>= 280 Fail Counts (25ms loop)	
			Ignition Voltage Low Hyst (run crank goes false when below this value)	2 Volts			Out of 280 Sample Counts (25ms loop)	
					ECM run/crank active status available ECM run/crank active status	= Vrai Boolean = Vrai Boolean		
					<b>Disable Condition s:</b> <b>MIL not Illuminated for DTC's:</b>	TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P2714	Pressure Control (PC) Solenoid D Stuck Off [CB26]	<u>Fail Case 1</u> Case: Steady State 2nd Gear  Gear slip  Intrusive test: commanded 3rd gear	>= 400 RPM			Please See Table Neutral >= 5 For Timer (Sec) I Time Cal	One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>If attained Gear = 3rd for Time</p> <p>If Above Conditions have been met</p> <p>Increment 2nd gear fail count</p> <p>and CB26 Fail Count</p>	<p>Table Based Time Enable Please see Table 2 in Supporting Documents (Sec)</p>			<p>&gt;= 3 2nd Gear Fail Count</p> <p>or</p> <p>&gt;= 14 CB26 Fail Count</p>	
			<p><u>Fail Case 2</u> Case: Steady State 6th Gear</p> <p>Gear slip</p> <p>Intrusive test: commanded 5th gear</p> <p>If attained Gear = 5th For Time</p>	<p>&gt;= 400 RPM</p> <p>Table Based Time Enable Please see Table 2 in Supporting Documents (Sec)</p>			<p>Please See Table Neutral &gt;= 5 For Timer (Sec)   Time Cal</p>	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Above Conditions have been met, Increment 5th gear fail counter  and CB26 Fail Count				>= 3 5th Gear Fail Count  or >= 14 CB26 Fail Count	
					PRNDL State defaulted inhibit RVT IMS fault pending indication TPS validity flag Hydraulic System Pressurized Minimum output speed for RVT A OR B (A) Output speed enable (B) Accelerator Pedal enable Common Enable Criteria Ignition Voltage Lo Ignition Voltage Hi Engine Speed Lo Engine Speed Hi Engine Speed is within the allowable limits for Throttle Position Signal valid HSD Enabled	= Faux Boolean = Faux Boolean = Faux Boolean = Vrai Boolean = Vrai Boolean >= 0 RPM >= 110 RPM >= 0.500488 Pct >= 9 Volts <= 31.99023 Volts >= 400 RPM <= 7500 RPM >= 5 Sec = Vrai Boolean = Vrai Boolean		



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Transmission Fluid Temperature Input Speed Sensor fault Output Speed Sensor fault Default Gear Option is not present  <b>MIL not Illuminated for DTC's:</b>	>= -6.65625 °C = Faux Boolean = Faux Boolean = Vrai  TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P2715	Pressure Control (PC) Solenoid D Stuck On [CB26] (Dynamic)	Primary Offgoing Clutch is exhausted (See Table 13 in Supporting Documents for Exhaust Delay Timers)  Primary Oncoming Clutch Pressure Command Status	= Vrai Boolean  = Maximum pressurized				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.	
			Primary Offgoing Clutch Pressure Command Status	=	Clutch exhaust command				
			Range Shift Status	≠	Initial Clutch Control				
			Attained Gear Slip	<=	40 RPM				
			If above coditons are true, increment appropriate Fail 1 Timers Below:						
			fail timer 1 (2-1 shifting with throttle)	>=	0.4003906	Fail Time (Sec)			
			fail timer 1 (2-1 shifting without throttle)	>=	0.5	Fail Time (Sec)			
			fail timer 1 (2-3 shifting with throttle)	>=	0.4003906	Fail Time (Sec)			
			fail timer 1 (2-3 shifting without throttle)	>=	0.5	Fail Time (Sec)			
			fail timer 1 (2-4 shifting with throttle)	>=	0.4003906	Fail Time (Sec)			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			fail timer 1 (2-4 shifting without throttle)	>= 0.5	Fail Time (Sec)			
			fail timer 1 (6-4 shifting with throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (6-4 shifting without throttle)	>= 0.5	Fail Time (Sec)			
			fail timer 1 (6-5 shifting with throttle)	>= 0.4003906	Fail Time (Sec)			
			fail timer 1 (6-5 shifting without throttle)	>= 0.5	Fail Time (Sec)			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Attained Gear Slip is Less than Above Cal Increment Fail Timers				Total Fail Time = (Fail 1 + Fail 2) See Enabl e Timers for Fail >= Timer    sec 1, and Refere nce Suppo rting Table 15 for Fail Timer 2	
			If fail timer is greater than threshold increment corresponding gear fail counter and total fail counter				Fail Counter >= 3 From 2nd Gear	
			2nd gear fail counter				OR	
			6th gear fail counter				Fail Counter >= 3 From 6th Gear	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			total fail counter				OR >= 3 Total Fail Counter	
					TUT Enable temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Command / Attained Gear	≠ 1st Boolean		
					High Side Driver ON	= Vrai Boolean		
					output speed limit for TUT	>= 200 RPM		
					input speed limit for TUT	>= 200 RPM		
					PRNDL state defaulted	= Faux Boolean		
					IMS Fault Pending	= Faux Boolean		
					Service Fast Learn Mode	= Faux Boolean		
					HSD Enabled	= Vrai Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:  MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P2715	Pressure Control (PC) Solenoid D Stuck On [CB26] (Steady State)	<u>Fail</u> <u>Case 1</u> Case: Steady State 1st	Attained Gear slip >= 400 RPM  Table Based Time Enab le If the Above is True for Time >= Please Refer to Time Table 4 in (Sec) supporting documents  Intrusive test: (CBR1 clutch exhausted)  Gear Ratio <= 3.1118164 Gear Ratio >= 2.7045898  If the above parameters are true				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
							>= 1.1 Fail Timer (Sec)  >= 5 Fail Count in 1st Gear  or  >= 5 Total Fail Counts	
			<u>Fail Case 2</u> Case: Steady State 3rd Gear					
			Max Delta Output Speed Hysteresis	Table Based value Please rpm/s Refer to 3D ec Table 1 in supporting documents				
			Min Delta Output Speed Hysteresis	Table Based value Please rpm/s Refer to 3D ec Table 2 in supporting documents				
			If the Above is True for Time	Table Based Time Please Sec Refer to Table 17 in supporting documents				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Intrusive test: (C35R clutch exhausted)  Gear Ratio <= 3.1118164 Gear Ratio >= 2.7045898  If the above parameters are true				>= 1.1 Fail Timer (Sec)  >= 3 Fail Count in 3rd Gear or >= 5 Total Fail Counts	
			<u>Fail</u> <u>Case 3</u> Case: Steady State 4rd Gear   Max Delta Output Speed Hysteresis >=	Table Based value Please rpm/s Refer to 3D ec Table 1 in supporting documents				
			Min Delta Output Speed Hysteresis >=	Table Based value Please rpm/s Refer to 3D ec Table 2 in supporting documents				



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>If the Above is True for Time</p> <p>Intrusive test: (C1234 clutch exhausted)</p> <p>Gear Ratio</p> <p>Gear Ratio</p> <p>If the above parameters are true</p>	<p>Table Based Time Please Refer to Table 17 in supporting documents</p> <p>&gt;= Sec</p> <p>&lt;= 0.7983398</p> <p>&gt;= 0.6938477</p>			<p>&gt;= 1.1 Fail Timer (Sec)</p> <p>&gt;= 3 Fail Count in 4th Gear</p> <p>or</p> <p>&gt;= 5 Total Fail Counts</p>	
			<p><u>Fail</u> <u>Case 4</u> Case: Steady State 5th Gear</p> <p>Max Delta Output Speed Hysteresis</p>	<p>Table Based value Please Refer to 3D ec Table 1 in supporting documents</p> <p>&gt;= rpm/s</p>				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Min Delta Output Speed Hysteresis	Table Based value Please Refer to 3D ec Table 2 in supporting documents rpm/s >=				
			If the Above is True for Time	Table Based Time Please Refer to Table 17 in supporting documents Sec >=				
			Intrusive test: (C35R clutch exhausted)					
			Gear Ratio	<= 0.7983398				
			Gear Ratio	>= 0.6938477				
			If the above parameters are true					
							>= 1.1	Fail Timer (Sec)
							>= 3	Fail Count in 5th Gear
							>= 5	or Total Fail Counts
					PRNDL State defaulted	= Faux Boolean		
					inhibit RVT	= Faux Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					IMS fault pending indication	= Faux Boolean		
					output speed	>= 0 RPM		
					TPS validity flag	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		
					Hydraulic_System_Pressurized	= Vrai Boolean		
					A OR B			
					(A) Output speed enable	>= 110 Nm		
					(B) Accelerator Pedal enable	>= 0.500488 Nm		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					if Attained Gear=1st FW Accelerator Pedal enable	>= 10.00061 Pct		
					if Attained Gear=1st FW Engine Torque Enable	>= 45 Nm		
					if Attained Gear=1st FW Engine Torque Enable	<= 8191.875 Nm		
					Transmission Fluid Temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Default Gear Option is not present	= Vrai		
					<b>Disable Condition s:</b>	<b>MIL not Illuminated for DTC's:</b> TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P2720	Pressure Control (PC) Solenoid D Control Circuit Low (CB26 VBS)	The HWIO reports a low voltage (ground short) error flag	= Vrai Boolean			>= 0.3 Fail Time (Sec)	One Trip
							out of 0.375 Sample Time (Sec)	
					P2770 Status is not	= Test Failed This Key On or Fault Active		
					Ignition Voltage	>= 9 Volts		
					Ignition Voltage	<= 31.99023 Volts		
					Engine Speed	>= 400 RPM		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed Engine Speed is within the allowable limits for	<= 7500 RPM >= 5 Sec MIL not illuminated for DTC's: TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P2721	Pressure Control (PC) Solenoid D Control Circuit High (CB26 VBS)	The HWIO reports a high voltage (open or power short) error flag	= Vrai Boolean			>= 0.3 Fail Time (Sec) out of 0.375 Sample Time (Sec)	One Trip
					P2721 Status is not = Test Failed This Key On or Fault Active Ignition Voltage >= 9 Volts Ignition Voltage <= 31.99023 Volts Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec MIL not illuminated for DTC's: TCM: None ECM: None			

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
Variable Bleed Solenoid (VBS)	P2723	Pressure Control (PC) Solenoid E Stuck Off	<u>Fail</u> <u>Case 1</u> Case: Steady State 1st Gear					One Trip
			Gear slip	>= 400 RPM				
			Intrusive test: commanded 2nd gear					
			If attained Gear ≠ 2nd for Time	>=	Please refer to Table 3 in Shift Supporting Time Documents (Sec)			
			If Above Conditions have been met, Increment 1st gear fail counter				>= 2	1st Gear Fail Count
			and C1234 fail counter				>= 14	or C1234 Clutch Fail Count
			<u>Fail</u> <u>Case 2</u> Case: Steady State 2nd Gear					
			Gear slip	>= 400 RPM				Please See Table Neutral >= 5 For Timer Neutra (Sec) I Time Cal

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>Intrusive test: commanded 3rd gear</p> <p>If attained Gear ≠ 3rd for Time &gt;=</p> <p>If Above Conditions have been met, Increment 2nd gear fail counter</p> <p>and C1234 fail counter</p>	<p>Please refer to Shift Table 3 in Time Supporting (Sec) Documents</p>			<p>&gt;= 2 2nd Gear Fail Count</p> <p>or</p> <p>&gt;= 14 C1234 Clutch Fail Count</p>	
			<p><u>Fail</u> <u>Case 3</u> Case: Steady State 3rd Gear</p> <p>Gear slip &gt;=</p> <p>Intrusive test: commanded 4th gear</p> <p>If attained Gear ≠ 4th for time &gt;=</p>	<p>400 RPM</p> <p>Please refer to Shift Table 3 in Time Supporting (Sec) Documents</p>			<p>Please See Table Neutral &gt;= 5 For Timer Neutra (Sec) l Time Cal</p>	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Above Conditions have been met, Increment 3rd gear fail counter				>= 2 3rd Gear Fail Count	
			and C1234 fail counter				>= 14 C1234 Clutch Fail Count	
			<u>Fail</u> <u>Case 4</u> Case: Steady State 4th Gear					
			Gear slip	>= 400 RPM			Please See Table Neutral >= 5 For Timer Neutra (Sec) l Time Cal	
			Intrusive test: commanded 5th gear					
			If attained Gear = 5th For Time	>=	Please refer to Shift Table 3 in Time Supporting (Sec) Documents			
			If Above Conditions have been met, Increment 4th gear fail counter				>= 3 4th Gear Fail Count	
			and C1234 fail counter				>= 14 C1234 Clutch Fail Count	
					PRNDL State defaulted	= Faux Boolean		



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					inhibit RVT	= Faux Boolean		
					IMS fault pending indication	= Faux Boolean		
					TPS validity flag	= Vrai Boolean		
					Hydraulic System Pressurized	= Vrai Boolean		
					Minimum output speed for RVT	>= 0 RPM		
					A OR B			
					(A) Output speed enable	>= 110 RPM		
					(B) Accelerator Pedal enable	>= 0.500488 Pct		
					Common Enable Criteria			
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					Throttle Position Signal valid	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		
					Transmission Fluid Temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Default Gear Option is not present	= Vrai		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Disa ble Con diti on s:	MIL not Illuminated for DTC's:  TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P2724	Pressure Control (PC) Solenoid E Stuck On (Dynamic)	Primary Offgoing Clutch is exhausted (See Table 10 in Supporting Documents for Exhaust Delay Timers)  Primary Oncoming Clutch Pressure Command Status  Primary Offgoing Clutch Pressure Command Status  Range Shift Status  Attained Gear Slip	=  =  =  ≠  <=	Vrai  Boo lean  Maximum pressurized  Clutch exhaust command  Initial Clutch Control  40 RPM			One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If the above conditions are true increment appropriate Fail 1 Timers Below:					
			fail timer 1 (2-6 shifting with throttle)	>= 0.4003906 sec				
			fail timer 1 (2-6 shifting without throttle)	>= 0.5 sec				
			fail timer 1 (3-5 shifting with throttle)	>= 0.4003906 sec				
			fail timer 1 (3-5 shifting without throttle)	>= 0.5 sec				
			fail timer 1 (4-5 shifting with throttle)	>= 0.4003906 sec				
			fail timer 1 (4-5 shifting without throttle)	>= 0.5 sec				
			fail timer 1 (4-6 shifting with throttle)	>= 0.4003906 sec				
			fail timer 1 (4-6 shifting without throttle)	>= 0.5 sec				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			If Attained Gear Slip is Less than Above Cal Increment Fail Timers				Total Fail Time = (Fail 1 + Fail 2) See Enabl e Timers for Fail >= Timer    sec 1, and Refere nce Suppo rting Table 15 for Fail Timer 2	
			If fail timer is greater than threshold increment corresponding gear fail counter and total fail counter					
			2nd gear fail counter				>= 3    Fail Counter From 2nd Gear	
			3rd gear fail counter				>= 3    Fail Counter From 3rd Gear	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			4th gear fail counter				>= 3	Fail Counter From 4th Gear
			total fail counter				>= 3	Total Fail Counter
					TUT Enable temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		
					Command / Attained Gear	≠ 1st Boolean		
					High Side Driver ON	= Vrai Boolean		
					output speed limit for TUT	>= 200 RPM		
					input speed limit for TUT	>= 200 RPM		
					PRNDL state defaulted	= Faux Boolean		
					IMS Fault Pending	= Faux Boolean		
					Service Fast Learn Mode	= Faux Boolean		
					HSD Enabled	= Vrai Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
				Dis able Con dition s:	MIL not Illuminated for DTC's:	TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P2724	Pressure Control (PC) Solenoid E Stuck On (Steady State)	<u>Fail</u> <u>Case 1</u>  Case: 5th Gear	Table Based value Please rpm/s >= Refer to 3D ec Table 1 in supporting documents  Table Based value Please rpm/s >= Refer to 3D ec Table 2 in supporting documents				One Trip

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			<p>If the Above is True for Time</p> <p>Intrusive test: (C35R clutch exhausted)</p> <p>Gear Ratio</p> <p>Gear Ratio</p> <p>If the above parameters are true</p>	<p>Table Based Time Please Refer to Table 17 in supporting documents</p> <p>&gt;= Sec</p> <p>&lt;= 1.5474854</p> <p>&gt;= 1.3450928</p>			<p>&gt;= 1.1 Fail Timer (Sec)</p> <p>&gt;= 3 Fail Count in 5th Gear</p> <p>OR</p> <p>&gt;= 3 Total Fail Counts</p>	
			<p><u>Fail</u> <u>Case 2</u> Case: 6th Gear</p> <p>Max Delta Output Speed Hysteresis</p>	<p>Table Based value Please Refer to 3D Table 1 in supporting documents</p> <p>&gt;= rpm/s ec</p>				

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
			Min Delta Output Speed Hysteresis	>=	Table Based value Please rpm/s Refer to 3D ec Table 2 in supporting documents			
			If the Above is True for Time	>=	Table Based Time Please Sec Refer to Table 17 in supporting documents			
			Intrusive test: (CB26 clutch exhausted)					
			Gear Ratio	<=	1.5474854			
			Gear Ratio	>=	1.3450928			
			If the above parameters are true					
							>= 1.1	Fail Timer (Sec)
							>= 3	Fail Count in 6th Gear
							>= 3	OR Total Fail Counts
					PRNDL State defaulted	= Faux Boolean		
					inhibit RVT	= Faux Boolean		



13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					IMS fault pending indication	= Faux Boolean		
					output speed	>= 0 RPM		
					TPS validity flag	= Vrai Boolean		
					HSD Enabled	= Vrai Boolean		
					Hydraulic_System_Pressurized	= Vrai Boolean		
					A OR B			
					(A) Output speed enable	>= 110 Nm		
					(B) Accelerator Pedal enable	>= 0.500488 Nm		
					Ignition Voltage Lo	>= 9 Volts		
					Ignition Voltage Hi	<= 31.99023 Volts		
					Engine Speed Lo	>= 400 RPM		
					Engine Speed Hi	<= 7500 RPM		
					Engine Speed is within the allowable limits for	>= 5 Sec		
					if Attained Gear=1st FW Accelerator Pedal enable	>= 10.00061 Pct		
					if Attained Gear=1st FW Engine Torque Enable	>= 45 Nm		
					if Attained Gear=1st FW Engine Torque Enable	<= 8191.875 Nm		
					Transmission Fluid Temperature	>= -6.65625 °C		
					Input Speed Sensor fault	= Faux Boolean		
					Output Speed Sensor fault	= Faux Boolean		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Default Gear Option is not present  MIL not illuminated for DTC's:	= Vrai  TCM: P0716, P0717, P0722, P0723, P182E  ECM: P0101, P0102, P0103, P0106, P0107, P0108, P0171, P0172, P0174, P0175, P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308, P0401, P042E		
Variable Bleed Solenoid (VBS)	P2729	Pressure Control (PC) Solenoid E Control Circuit Low (C1234 VBS)	The HWIO reports a low voltage (ground short) error flag	= Vrai Boolean			>= 0.3 Fail Time (Sec)  out of 0.375 Sample Time (Sec)	One Trip
					P2729 Status is not	=		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					Engine Speed is within the allowable limits for	>= 5 Sec		
					<b>Disable Condition s:</b> MIL not Illuminated for DTC's:	TCM: None ECM: None		
Variable Bleed Solenoid (VBS)	P2730	Pressure Control (PC) Solenoid E Control Circuit High (C1234 VBS)	The HWIO reports a high voltage (open or power short) error flag	= Vrai Boolean			>= 0.3 Fail Time (Sec) out of 0.375 Sample Time (Sec)	One Trip
					P2730 Status is not = Test Failed This Key On or Fault Active	Ignition Voltage >= 9 Volt Ignition Voltage <= 31.99023 Volt Engine Speed >= 400 RPM Engine Speed <= 7500 RPM Engine Speed is within the allowable limits for >= 5 Sec	TCM: None ECM: None	
					<b>Disable Condition s:</b> MIL not Illuminated for DTC's:	TCM: None ECM: None		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.	
Variable Bleed Solenoid (VBS)	P2763	Torque Converter Clutch Pressure High	The HWIO reports a low pressure/high voltage (open or power short) error flag	=	Vrai	Boolean	>= 4.4 out of 5	Fail Time (Sec) Sample Time (Sec)	Two Trips
Variable Bleed Solenoid (VBS)	P2764	Torque Converter Clutch Pressure Control Solenoid Control Circuit Low	The HWIO reports a high pressure/low voltage (ground short) error flag	=	Vrai	Boolean	>= 4.4 MPH out of 5 MPH	One Trip	

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					P2764 Status is not  Ignition Voltage Ignition Voltage Engine Speed Engine Speed Engine Speed is within the allowable limits for High Side Driver Enabled	= Test Failed This Key On or Fault Active  >= 9 Volt <= 31.99023 Volt >= 400 RPM <= 7500 RPM >= 5 Sec = Vrai Boolean		
					<b>Disa ble Con diti on s:</b>	<b>MIL not Illuminated for DTC's:</b> TCM: P0658, P0659 ECM: None		
Communication	U0073	Controller Area Network Bus Communication Error	CAN Hardware Circuitry Detects a Low Voltage Error	= Vrai Boolean			>= 62 Fail counts (≈ 10 second s)  Out of 70 Sample Counts (≈ 11 second s)	One Trip
			Delay timer	>= 0.1125 sec				
					Stabilization delay Ignition Voltage Ignition Voltage Power Mode	>= 3 sec >= 9 Volt <= 31.99023 Volt = Run		

13 OBDG02A Transmission Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Malfunction	Enable Conditions	Time Required	Mil Illum.
					<b>MIL not Illuminated for DTC's:</b>	TCM: None ECM: None		
Communication	U0100	Lost Communications with ECM (Engine Control Module)	CAN messages from ECM are not received by the TCM	= Vrai Boolean			>= 12 sec	One Trip
					Stabilization delay Ignition Voltage Ignition Voltage Power Mode	>= 3 sec >= 9 Volt <= 31.99023 Volt = Run		
					<b>MIL not Illuminated for DTC's:</b>	TCM: U0073 ECM: None		

## 13 OBDG02A Transmission Diagnostics

Supporting Documents - 2D TablesTable 1

KtTCCD_n_StuckOffFailLimit KtTCCD_n_StuckOffFailLimit	Axis	0.00	64.00	128.00	192.00	256.00	320.00	384.00	448.00	512.00	N*m
	Curve	100.00	120.00	150.00	150.00	150.00	150.00	150.00	150.00	150.00	150.00

Table 2

KnRSSC_T_RVT_TransTempAxis KtRSSC_t_INT_EstGear	Axis	-6.67	-6.66	40.00	°C
	Curve	409.59	2.00	2.00	Sec

Table 3

KnRSSC_T_RVT_TransTempAxis KtRSSC_t_INT_ShiftTime	Axis	-6.67	-6.66	40.00	°C
	Curve	409.59	3.50	3.50	Sec

Table 4

KnRSSC_T_RVT_TransTempAxis KtRSSC_t_TUT_NeutralTime	Axis	-6.67	-6.66	40.00	°C
	Curve	409.59	2.99	2.00	Sec

Table 5

KnRSSC_T_RVT_TransTempAxis KtRSSC_t_INT_NeutralTime	Axis	-6.67	-6.66	40.00	°C
	Curve	409.59	3.00	3.00	Sec

Table 6

KnDGSC_T_TransTempAxis KtDGSC_t_S1_TestDelayLimit	Axis	-6.67	-6.66	40.00	80.00	120.00	°C
	Curve	409.00	3.60	1.60	1.40	1.40	Sec

Table 7

KnDGSC_T_TransTempAxis KtDGSC_t_S2_TestDelayLimit	Axis	-6.67	-6.66	40.00	80.00	120.00	°C
	Curve	409.00	3.40	1.40	1.30	1.20	Sec

Table 8

KnDGSC_T_TransTempAxis KtDGSC_t_S3_TestDelayLimit	Axis	-6.67	-6.66	40.00	80.00	120.00	°C
	Curve	409.00	3.60	1.60	1.50	1.40	Sec

## 13 OBDG02A Transmission Diagnostics

Supporting Documents - 2D Tables**Table 9**

KnDGSC_T_TransTempAxis KtDGSC_t_S4_TestDelayLimit	Axis	-6.67	-6.66	40.00	80.00	120.00	°C
	Curve	409.00	3.30	1.30	1.20	1.10	Sec

**Table 10**

KnRSCC_T_TransFluidTempAxis KtRSCC_t_C1_OffgoingNoCapTmr	Axis	-40.00	-20.00	0.00	30.00	110.00	°C
	Curve	8.85	3.75	1.31	0.28	0.28	Sec

**Table 11**

KnRSCC_T_TransFluidTempAxis KtRSCC_t_C2_OffgoingNoCapTmr	Axis	-40.00	-20.00	0.00	30.00	110.00	°C
	Curve	5.00	1.70	0.40	0.25	0.25	Sec

**Table 12**

KnRSCC_T_TransFluidTempAxis KtRSCC_t_C3_OffgoingNoCapTmr	Axis	-40.00	-20.00	0.00	30.00	110.00	°C
	Curve	8.00	2.20	0.70	0.25	0.25	Sec

**Table 13**

KnRSCC_T_TransFluidTempAxis KtRSCC_t_C4_OffgoingNoCapTmr	Axis	-40.00	-20.00	0.00	30.00	110.00	°C
	Curve	5.20	1.60	0.50	0.27	0.16	Sec

**Table 14**

KnRSCC_T_TransFluidTempAxis KtRSCC_t_C5_OffgoingNoCapTmr	Axis	-40.00	-20.00	0.00	30.00	110.00	°C
	Curve	5.00	1.50	0.70	0.25	0.25	Sec

**Table 15**

KeRSCC_t_12RngDiagFailDeltTbl KeRSCC_t_12RngDiagFailDeltTbl	Axis	-40.00	-30.00	-20.00	-10.00	0.00	10.00	20.00	30.00	40.00	°C
	Curve	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	Sec

**Table 16**

KnRSCC_T_RVT_TransTempAxis KtRSCC_t_M2V_StuckOnNeutralTime	Axis	-6.67	-6.66	40.00	°C
	Curve	409.59	2.50	2.50	Sec



## 13 OBDG02A Transmission Diagnostics

Supporting Documents - 2D Tables**Table 17**

KnRSSC_T_RVT_TransTempAxis KtRSSC_t_SS_DecelHystTime	<b>Axis</b>	-6.67	-6.66	40.00	°C
	<b>Curve</b>	0.40	0.35	0.30	Sec

**Table 18**

KnTFTD_T_RatlCheckTempAxis KtTFTD_T_OilPwrUpMaxDelta	<b>Axis</b>	-40.10	-40.00	-20.00	0.00	30.00	60.00	100.00	149.00	149.10	°C
	<b>Curve</b>	256.00	50.00	45.00	40.00	34.00	25.00	20.00	20.00	256.00	°C

**Table 19**

KnTFTD_T_RatlCheckTempAxis KtTFTD_T_OilSubMaxDelta	<b>Axis</b>	-40.10	-40.00	-20.00	0.00	30.00	60.00	100.00	149.00	149.10	°C
	<b>Curve</b>	256.00	50.00	45.00	40.00	34.00	25.00	20.00	20.00	256.00	°C

**Table 20**

KnTFTD_T_RatlCheckTempAxis KtTFTD_T_SubPwrUpMaxDelta	<b>Axis</b>	-40.10	-40.00	-20.00	0.00	30.00	60.00	100.00	149.00	149.10	°C
	<b>Curve</b>	256.00	10.00	8.00	8.00	8.00	8.00	8.00	8.00	8.00	256.00

**Table 21**

KnTOSI_T_DirctnChgTempAxis KtTOSI_t_DirctnChgDelayTime	<b>Axis</b>	-40.00	-20.00	40.00	°C
	<b>Curve</b>	5.00	3.00	1.00	Sec

13 OBDG02A Transmission Diagnostics

**Supporting Documents - 3D Tables**

3D\_Table 1

KnRSSC_Pct_StartleThrotAxis	X-Axis Calibration	%
KnRSSC_T_RVT_TransTempAxis	Y-Axis Calibration	°C
KtRSSC_dn_StartleDecelMax	Table Calibration	RPM/Sec

	0.00	2.00	5.00	25.00	100.00
-6.67	8191.75	8191.75	8191.75	8191.75	8191.75
-6.66	8191.75	8191.75	8191.75	8191.75	8191.75
40.00	8191.75	8191.75	8191.75	8191.75	8191.75

3D\_Table 2

KnRSSC_Pct_StartleThrotAxis	X-Axis Calibration	%
KnRSSC_T_RVT_TransTempAxis	Y-Axis Calibration	°C
KtRSSC_dn_StartleDecelMin	Table Calibration	RPM/Sec

	0.00	2.00	5.00	25.00	100.00
-6.67	8191.75	8191.75	8191.75	8191.75	8191.75
-6.66	500.00	500.00	300.00	300.00	300.00
40.00	500.00	500.00	300.00	300.00	300.00